

UNIVERSAL GREASE

ISO 12924: L-XC(F)CIB2 | DIN 51502: KP2K-30

Article #	EAN	Product
895039	3660338474316	Universal Grease (400g)
895040	3660338474323	Universal Grease (900g)

Description

Spartex Universal Grease is an anhydrous calcium thickened lubricating grease based on a mineral oil. The grease contains antioxidants, corrosion inhibitors & EP/AW additives.

The thickener together with the special base oil blend makes the product suitable for the lubrication of medium loaded bearings and in wet & corrosive environments. The lubricating grease has excellent adhesion and water resistance.

895039 / 895040 is a high quality universal grease that can be used in both industrial & automotive applications. The grease is suitable for a wide range of plain and rolling bearings.



WATER RESISTANCE | CORROSION PROTECTION | MULTI USE

Typical Properties

Characteristic	Method	Result
Thickener		Anhydrous calcium
Base Fluid		Mineral oil
Texture		Smooth
Colour	Visual	Amber
NLGI Grade	ASTM D 217 mod	2
Dropping Point, °C	IP 396	> 140
Density, Kg/m ³	IP 530	900
Temperature range, °C		-30 to 120
Base Oil Viscosity at 40°C, cSt	ASTM D 7152	110
Base Oil Viscosity at 100°C, cSt	ASTM D 7152	9
Penetration 60 strokes	ISO 2137	265 – 295
4-ball weld load, N	DIN 51350:4	3000
Water wash out at 79°C, %	ISO 11009	< 10
Water resistance at 90°C	DIN 51807:1	0
Flow Pressure at -30°C, mbar	DIN 51805	< 1400
FE9 (B/130C/6000rpm/1500N)	DIN 51821	F50 ≥ 100h

Packaging

- Cartridge (400g)
- Pot (900g)