



Copper Tube Terminals



Features & Benefits

Manufactured to BS7609 (1992) Standards.
Bell mouth cable entry terminals to ensure easy entry. Electro tinned. Copper Conductivity to 99.9% I.A.C.S. Maximum operating temperature: 149°C.

Order Codes

CODE	DESCRIPTION	CABLE SIZE	STUD SIZE
630101	CT1.5M4	1.5	4
630102	CT1.5M5	1.5	5
630201	CT2.5M4	2.5	4
630202	CT2.5M5	2.5	5
630203	CT2.5M6	2.5	6
630301	CT4M4	4	4
630302	CT4M5	4	5
630303	CT4M6	4	6
630401	CT6M4	6	4
630402	CT6M5	6	5
630403	CT6M6	6	6
630404	CT6M8	6	8
630405	CT6M10	6	10
630502	CT10M5	10	5
630503	CT10M6	10	6
630504	CT10M8	10	8
630505	CT10M10	10	10
630506	CT10M12	10	12
630603	CT16M6	16	6
630604	CT16M8	16	8
630605	CT16M10	16	10
630606	CT16M11	16	12
630703	CT25M6	25	6
630704	CT25M8	25	8
630705	CT25M10	25	10
630706	CT25M12	25	12
630803	CT35M6	35	6
630804	CT35M8	35	8
630805	CT35M10	35	10
630806	CT35M12	35	12
630807	CT35M14	35	14
630903	CT50M6	50	6
630904	CT50M8	50	8
630905	CT50M10	50	10
630906	CT50M12	50	12
630907	CT50M14	50	14
630908	CT50M16	50	16

Order Codes

CODE	DESCRIPTION	CABLE SIZE	STUD SIZE
631003	CT70M6	70	6
631004	CT70M8	70	8
631005	CT70M10	70	10
631006	CT70M12	70	12
631007	CT70M14	70	14
631008	CT70M16	70	16
631009	CT70M20	70	20
631104	CT95M8	95	8
631105	CT95M10	95	10
631106	CT95M12	95	12
631107	CT95M14	95	14
631108	CT95M16	95	16
631109	CT95M20	95	20
631204	CT120M8	120	8
631205	CT120M10	120	10
631206	CT120M12	120	12
631207	CT120M14	120	14
631208	CT120M16	120	16
631209	CT120M20	120	20
631305	CT150M10	150	10
631306	CT150M12	150	12
631307	CT150M14	150	14
631308	CT150M16	150	16
631309	CT150M20	150	20
631405	CT185M10	185	10
631406	CT185M12	185	12
631407	CT185M14	185	14
631408	CT185M16	185	16
631505	CT240M10	240	10
631506	CT240M12	240	12
631507	CT240M14	240	14
631508	CT240M16	240	16
631605	CT300M10	300	10
631606	CT300M12	300	12
631608	CT300M16	300	16
631706	CT400M12	400	12

Copper Tube Splices



Features & Benefits

Manufactured to BS7609 (1992) Standards.
Bell mouth cable entry terminals to ensure easy entry. Electro tinned. Copper Conductivity to 99.9% I.A.C.S. Maximum operating temperature: 149°C.

Order Codes

CODE	DESCRIPTION	CABLE SIZES
635001	Copper Tube Splices	1.5
635002	Copper Tube Splices	2.5
635003	Copper Tube Splices	4
635004	Copper Tube Splices	6
635005	Copper Tube Splices	10
635006	Copper Tube Splices	16
635007	Copper Tube Splices	25
635008	Copper Tube Splices	35
635009	Copper Tube Splices	50
635010	Copper Tube Splices	70
635011	Copper Tube Splices	95
635012	Copper Tube Splices	120
635013	Copper Tube Splices	150
635014	Copper Tube Splices	185
635015	Copper Tube Splices	240
635016	Copper Tube Splices	300