

316L Plug-In Reducer 001 002 <table border="1"> <tr><td>4</td><td>6</td><td>3168 04 06</td></tr> <tr><td>6</td><td>8</td><td>3186 06 08</td></tr> <tr><td>8</td><td>10</td><td>3186 08 10</td></tr> <tr><td>10</td><td>12</td><td>3186 10 12</td></tr> <tr><td>12</td><td>14</td><td>3186 10 14</td></tr> <tr><td>14</td><td>16</td><td>3186 12 14</td></tr> </table>	4	6	3168 04 06	6	8	3186 06 08	8	10	3186 08 10	10	12	3186 10 12	12	14	3186 10 14	14	16	3186 12 14	001 002 Plug-In In-Reducer 001 002 <table border="1"> <tr><td>4</td><td>6</td><td>3168 04 04</td></tr> <tr><td>6</td><td>8</td><td>3186 06 06</td></tr> <tr><td>8</td><td>10</td><td>3186 08 08</td></tr> <tr><td>10</td><td>12</td><td>3186 10 08</td></tr> </table>	4	6	3168 04 04	6	8	3186 06 06	8	10	3186 08 08	10	12	3186 10 08	3118 Single Banjo, Male BSSP and Metric Thrust 00 C <table border="1"> <tr><td>4</td><td>Mx5/8</td><td>3118 04 19"</td></tr> <tr><td>6</td><td>G1/8</td><td>3118 06 14"</td></tr> <tr><td>8</td><td>Mx5/8</td><td>3118 06 19"</td></tr> <tr><td>6</td><td>G1/8</td><td>3118 06 10"</td></tr> <tr><td>8</td><td>G1/8</td><td>3118 06 13</td></tr> <tr><td>10</td><td>G1/8</td><td>3118 06 10</td></tr> <tr><td>12</td><td>G3/8</td><td>3118 06 17</td></tr> <tr><td>14</td><td>G1/4</td><td>3118 10 13</td></tr> <tr><td>16</td><td>G3/8</td><td>3118 10 17</td></tr> </table> <i>"With screwdriver slot"</i>	4	Mx5/8	3118 04 19"	6	G1/8	3118 06 14"	8	Mx5/8	3118 06 19"	6	G1/8	3118 06 10"	8	G1/8	3118 06 13	10	G1/8	3118 06 10	12	G3/8	3118 06 17	14	G1/4	3118 10 13	16	G3/8	3118 10 17	3310 In-Line Manifold 00 C <table border="1"> <tr><td>4</td><td>G1/4</td><td>3310 04 13</td></tr> <tr><td>6</td><td>G1/4</td><td>3310 06 17</td></tr> <tr><td>8</td><td>G3/8</td><td>3310 08 13</td></tr> <tr><td>10</td><td>G1/2</td><td>3310 10 21</td></tr> <tr><td>12</td><td>G1/2</td><td>3310 12 21</td></tr> </table>	4	G1/4	3310 04 13	6	G1/4	3310 06 17	8	G3/8	3310 08 13	10	G1/2	3310 10 21	12	G1/2	3310 12 21
4	6	3168 04 06																																																																									
6	8	3186 06 08																																																																									
8	10	3186 08 10																																																																									
10	12	3186 10 12																																																																									
12	14	3186 10 14																																																																									
14	16	3186 12 14																																																																									
4	6	3168 04 04																																																																									
6	8	3186 06 06																																																																									
8	10	3186 08 08																																																																									
10	12	3186 10 08																																																																									
4	Mx5/8	3118 04 19"																																																																									
6	G1/8	3118 06 14"																																																																									
8	Mx5/8	3118 06 19"																																																																									
6	G1/8	3118 06 10"																																																																									
8	G1/8	3118 06 13																																																																									
10	G1/8	3118 06 10																																																																									
12	G3/8	3118 06 17																																																																									
14	G1/4	3118 10 13																																																																									
16	G3/8	3118 10 17																																																																									
4	G1/4	3310 04 13																																																																									
6	G1/4	3310 06 17																																																																									
8	G3/8	3310 08 13																																																																									
10	G1/2	3310 10 21																																																																									
12	G1/2	3310 12 21																																																																									
3182 Equal and Unequal Plug-In Elbow 001 002 <table border="1"> <tr><td>4</td><td>6</td><td>3182 04 06</td></tr> <tr><td>6</td><td>8</td><td>3182 06 08</td></tr> <tr><td>8</td><td>10</td><td>3182 08 10</td></tr> <tr><td>10</td><td>12</td><td>3182 10 12</td></tr> <tr><td>12</td><td>14</td><td>3182 12 10</td></tr> </table>	4	6	3182 04 06	6	8	3182 06 08	8	10	3182 08 10	10	12	3182 10 12	12	14	3182 12 10	001 Blanking Plug 00 <table border="1"> <tr><td>4</td><td>3126 04 00</td></tr> <tr><td>6</td><td>3126 06 00</td></tr> <tr><td>8</td><td>3126 08 00</td></tr> <tr><td>10</td><td>3126 10 00</td></tr> <tr><td>12</td><td>3126 12 00</td></tr> </table>	4	3126 04 00	6	3126 06 00	8	3126 08 00	10	3126 10 00	12	3126 12 00	3100 Carisak® Cartridge 00 C <table border="1"> <tr><td>4</td><td>3100 04 00</td></tr> <tr><td>6</td><td>3100 06 00</td></tr> <tr><td>8</td><td>3100 08 00</td></tr> <tr><td>10</td><td>3100 10 00</td></tr> <tr><td>12</td><td>3100 12 00</td></tr> <tr><td>14</td><td>3100 14 00</td></tr> </table>	4	3100 04 00	6	3100 06 00	8	3100 08 00	10	3100 10 00	12	3100 12 00	14	3100 14 00	3311 Manifold, Female BSSP and Metric Thrust C1 C2 <table border="1"> <tr><td>G1/4</td><td>Mx5/8</td><td>3311 19 07</td></tr> <tr><td></td><td></td><td>3311 10 13 02</td></tr> <tr><td></td><td></td><td>3311 10 13 02</td></tr> <tr><td></td><td></td><td>3311 10 13 04</td></tr> <tr><td></td><td></td><td>3311 10 13 05</td></tr> <tr><td></td><td></td><td>3311 10 13 06</td></tr> <tr><td></td><td></td><td>3311 13 17 02</td></tr> <tr><td></td><td></td><td>3311 13 17 03</td></tr> <tr><td>G3/8</td><td>G1/4</td><td>3311 13 17 04</td></tr> <tr><td></td><td></td><td>3311 13 17 05</td></tr> </table>	G1/4	Mx5/8	3311 19 07			3311 10 13 02			3311 10 13 02			3311 10 13 04			3311 10 13 05			3311 10 13 06			3311 13 17 02			3311 13 17 03	G3/8	G1/4	3311 13 17 04			3311 13 17 05					
4	6	3182 04 06																																																																									
6	8	3182 06 08																																																																									
8	10	3182 08 10																																																																									
10	12	3182 10 12																																																																									
12	14	3182 12 10																																																																									
4	3126 04 00																																																																										
6	3126 06 00																																																																										
8	3126 08 00																																																																										
10	3126 10 00																																																																										
12	3126 12 00																																																																										
4	3100 04 00																																																																										
6	3100 06 00																																																																										
8	3100 08 00																																																																										
10	3100 10 00																																																																										
12	3100 12 00																																																																										
14	3100 14 00																																																																										
G1/4	Mx5/8	3311 19 07																																																																									
		3311 10 13 02																																																																									
		3311 10 13 02																																																																									
		3311 10 13 04																																																																									
		3311 10 13 05																																																																									
		3311 10 13 06																																																																									
		3311 13 17 02																																																																									
		3311 13 17 03																																																																									
G3/8	G1/4	3311 13 17 04																																																																									
		3311 13 17 05																																																																									
3304 Multiple Tee 001 002 <table border="1"> <tr><td>6</td><td>4</td><td>3304 06 04</td></tr> <tr><td>8</td><td>4</td><td>3304 08 04</td></tr> <tr><td>10</td><td>6</td><td>3304 10 06</td></tr> <tr><td>12</td><td>8</td><td>3304 12 08</td></tr> </table>	6	4	3304 06 04	8	4	3304 08 04	10	6	3304 10 06	12	8	3304 12 08	001 Tee 001 002 <table border="1"> <tr><td>6</td><td>4</td><td>3304 06 04</td></tr> <tr><td>8</td><td>4</td><td>3304 08 04</td></tr> <tr><td>10</td><td>6</td><td>3304 10 06</td></tr> <tr><td>12</td><td>8</td><td>3304 12 08</td></tr> </table>	6	4	3304 06 04	8	4	3304 08 04	10	6	3304 10 06	12	8	3304 12 08																																																		
6	4	3304 06 04																																																																									
8	4	3304 08 04																																																																									
10	6	3304 10 06																																																																									
12	8	3304 12 08																																																																									
6	4	3304 06 04																																																																									
8	4	3304 08 04																																																																									
10	6	3304 10 06																																																																									
12	8	3304 12 08																																																																									

Push-In Fittings

pressed air, grease, lubricant, water...
 100 psi / 7 bar (20 bar 3609, 3609)
 100°C +150°C
 chemical nickel-plated brass, PFM

3609



Stud Elbow, Male BSP Thread

ØD	C
4	R1/8 3609 04 10
6	R1/8 3609 06 10
8	R1/4 3609 08 10
10	R1/2 3609 10 10
12	R3/8 3609 12 10
14	R1/2 3609 14 10

3606



Equal Tube-to-Tube Connector

4	3606 04 00
6	3606 06 00
8	3606 08 00
10	3606 10 00
12	3606 12 00
14	3606 14 00

3600



One-Piece Cartridge

4	3600 04 00
6	3600 06 00
8	3600 08 00
10	3600 10 00
12	3600 12 00
14	3600 14 00

3699



Compact Elbow, Male BSP and Metric Thread

ØD	C
4	M5x0.8 3699 04 10
6	M5x1 3699 06 10
8	M6 3699 08 10
10	M6 3699 10 10
12	M8 3699 12 10
14	M8 3699 14 10

3602



Equal Elbow

ØD	C
4	3602 04 00
6	3602 06 00
8	3602 08 00
10	3602 10 00
12	3602 12 00
14	3602 14 00

3603



Stud Branch Tee, Male BSP and Metric Thread

ØD	C
4	M5x0.8 3603 04 10
6	M5x1 3603 06 10
8	M6 3603 08 10
10	M6 3603 10 10
12	M8 3603 12 10
14	M8 3603 14 10

3604



Equal Tee

ØD	C
4	3604 04 00
6	3604 06 00
8	3604 08 00
10	3604 10 00
12	3604 12 00
14	3604 14 00

3605



Equal Bulkhead Connector

ØD	C
4	3616 04 00
6	3616 06 00
8	3616 08 00
10	3616 10 00
12	3616 12 00
14	3616 14 00

3626



Blanking Plug

ØD	C
4	3626 04 00
6	3626 06 00
8	3626 08 00
10	3626 10 00
12	3626 12 00
14	3626 14 00

3698



Single Banjo, Male BSP and Metric Thread

ØD	C
4	M5x0.8 3698 04 10
6	M5x1 3698 06 10
8	M6 3698 08 10
10	M6 3698 10 10
12	M8 3698 12 10
14	M8 3698 14 10

3627



Bulkhead Connector, Female BSP Thread

ØD	C
4	3627 04 00
6	3627 06 00
8	3627 08 00
10	3627 10 00
12	3627 12 00
14	3627 14 00

3697



Extended Stud Elbow, Male BSP and Metric Thread

ØD	C
4	M5x0.8 3697 04 10
6	M5x1 3697 06 10
8	M6 3697 08 10
10	M6 3697 10 10
12	M8 3697 12 10
14	M8 3697 14 10

3628



Plug-In Barb Connector

ØD1	ØD2	C
4	3,2	3628 04 03
6	5	3628 06 05
8	6	3628 08 06
10	8	3628 10 08
12	10	3628 12 10
14	12,5	3628 14 12,5

Pneumatic Sensor Fittings		Pressure Regulators			
Compatible Fluids Compressed air Working Pressure 3 to 8 bar Working Temperature -15°C to +60°C Component Materials Technical polymer, brass, NBR		Compatible Fluids: Compressed air Working Pressure: Upstream pressure: 1 to 16 bar Downstream pressure: 1 to 8 bar Working Temperature: -10°C to +70°C Component Materials: Technical polymer, nickel-plated brass, nitride Silencers Compatible Fluids: Compressed air Working Pressure Polyethylene: 0 to 10 bar, Sintered bronze: 0 to 12 bar Working Temperature: Polyethylene: -10°C to +80°C Sintered bronze: -20°C to +150°C Component Materials Sintered bronze, brass, technical polymer			
7018 Pneumatic Sensor Fitting, Male BSP and Metric Thread		7028 Pneumatic/Electric Sensor, Male/Female BSP and Metric Thread			
7018 Pneumatic Sensor Fitting, Male BSP and Metric Thread		7028 Pneumatic/Electric Sensor, Male/Female BSP and Metric Thread			
Compatible Fluids: Compressed air Working Pressure: 1 to 10 bar Working Temperature: -5°C to +60°C Component Materials: Technical polymer, nickel-plated brass, NBR		7300 Pressure Regulator, Male BSP Thread			
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					
7300 Pressure Regulator, Male BSP Thread					

Industrial Blowing Guns

Compatible Fluids	Compressed air
Working Pressure	0 to 10 bar
Working Temperature	-15°C to +50°C
Technical Materials	Technical polymer, NBR

0459



Standard, Lower Connection, Short Angled Nozzle, Female BSPP Thread

C  

M1/4 3.5 0650 00 13

0454



Safety Straight Nozzle (Short)

C  

M1/4 3 0654 00 13

0453



Energy Saving Blowing Gun, Lower Connection, Female BSPP Thread

C  

M1/4 0653 06 13

0452



Progressive Control Blowing Gun, Lower Connection, Female BSPP Thread

C  

M1/4 0652 06 13

0470 01



Standard Nozzle

C  

M1/2x1.25 2.5 0690 01 00

0470 04



Safety Straight Nozzle (Short)

C  

M1/2x1.25 2.5 0690 04 00

0470 06



Safety Angled Nozzle (Short)

C  

M1/2x1.25 2.5 0690 06 00

0470 08



COANDA Nozzle

C  

M1/2x1.25 0690 08 00

0451 09



Blowgun Kit, Lower Connection, Female BSPT Thread

C 

R1/4 0631 00 09

0451 01



Safety Blowgun Kit, Lower Connection, Male BSPT Thread

C 

R1/4 0631 00 01

0451 23



Energy Saving Blowgun Kit, Angled Nozzle, Male BSPT Thread

C 

R1/4 0631 00 23

0451 07



Blowgun Kit, Lower Connection, Male BSPT Thread

C 

R1/4 0631 00 07

Maintenance Kits

3150 00 01 57



LF 3000 Kits BSPT products

3150 00 01 58



LF 3000 Kits BSPT products

3650 00 00 33



LF 3600 Kit

0450 00 00 02
0950 00 00 03



Accessories Kits
2 kits: BSPP (02) and BSPT products (03)

BRASS/STEEL QUICK CONNECT COUPLERS - EUROPEAN PROFILE

Suitable fluids	Working pressure	Working temperature	Material
Compressed air, all fluids compatible with the material	35 bar	-20°C up to +100°C (NBR) depending on the medium	Brass - Series 1625 and 1727: nickel-plated brass, QPQ treated steel, PAg+TPE Seals: NBR

Nominal Diameter 2,7 mm = 6 mm²

Series 20 165 NU/min

Couplers with valve

20KAA Coupler, male thread BSPP
C PN
G1/8 20KAAW13MPN
G1/8 20KAAW10MPN

20KAF Coupler, hose barb
I.D. hose PN
3 20KATF06MPN
4 20KATF08MPN
5 20KATF10MPN

20KAK Coupler, Plastic Hose Connection
3/4 20KAK04MPN
3/8 20KAK05MPN
3/8 20KAK06MPN

20KAP Coupler, Push-In
C PN
4 20KAP04MPN

Plugs without valve

20SA Coupler, male thread BSPP and metric
C PN
M5 20SFAW10MPN
G1/8 20SFAW10MPN

20SF Coupler, female thread BSPP and metric
C PN
M5 20SF06MPN
G1/8 20SF08MPN

20SFT Plug, hose barb
I.D. hose PN
3 20SFT06MPN
4 20SFT08MPN
5 20SFT10MPN

20SK Coupler, Panel Mount with Plastic Hose Connection
3/4 20SK04MPN
3/8 20SK05MPN
3/8 20SK06MPN

20SKT Coupler, Plastic Hose Connection
3/4 20SK04MPN
3/8 20SK05MPN
3/8 20SK06MPN

20SKP Coupler, Push-In
C PN
4 20SKP04MPN

Nominal Diameter 5 mm = 20 mm²

Series 21 550 NU/min

Couplers with valve

21KAA Coupler, male thread BSPP
C PN
G1/8 21KAAW13MPN
G1/8 21KAAW10MPN

21KAF Coupler, hose barb
I.D. hose PN
4 21KATF06MPN
5 21KATF08MPN
6 21KATF10MPN

21KAK Coupler, Plastic Hose Connection
3/4 21KAK04MPN
3/8 21KAK05MPN
3/8 21KAK06MPN

21KAP Coupler, Push-In
C PN
4 21KAP04MPN

Plugs without valve

21SA Coupler, male thread BSPP
C PN
M5 21SFAW10MPN
G1/8 21SFAW10MPN

21SF Coupler, female thread BSPP
C PN
M5 21SF06MPN
G1/8 21SF08MPN

21SFT Plug, hose barb
I.D. hose PN
3 21SFT06MPN
4 21SFT08MPN
5 21SFT10MPN

21SK Coupler, Panel Mount with Plastic Hose Connection
3/4 21SK04MPN
3/8 21SK05MPN
3/8 21SK06MPN

21SKT Coupler, Plastic Hose Connection
3/4 21SK04MPN
3/8 21SK05MPN
3/8 21SK06MPN

21SKP Coupler, Push-In
C PN
4 21SKP04MPN

Nominal Diameter 7,2 mm = 40 mm²

Series 26 1000 NU/min

Couplers with valve

26KAA Coupler, male thread BSPP
C PN
G1/4 26KAAW13MPN
G1/4 26KAAW10MPN

26KAF Coupler, hose barb
I.D. hose PN
6 26KATF06MPN
8 26KATF08MPN
10 26KATF10MPN

26KAK Coupler, Plastic Hose Connection
3/4 26KAK04MPN
3/8 26KAK05MPN
3/8 26KAK06MPN

26KAP Coupler, Push-In
C PN
4 26KAP04MPN

Plugs without valve

26SA Coupler, male thread BSPP
C PN
M5 26SFAW10MPN
G1/4 26SFAW10MPN

26SF Coupler, female thread BSPP
C PN
M5 26SF06MPN
G1/4 26SF08MPN

26SFT Plug, hose barb
I.D. hose PN
3 26SFT06MPN
4 26SFT08MPN
5 26SFT10MPN

26SK Coupler, Panel Mount with Plastic Hose Connection
3/4 26SK04MPN
3/8 26SK05MPN
3/8 26SK06MPN

26SKT Coupler, Plastic Hose Connection
3/4 26SK04MPN
3/8 26SK05MPN
3/8 26SK06MPN

26SKP Coupler, Push-In
C PN
4 26SKP04MPN

Nominal Diameter 7,8 mm = 48 mm²

Series 25 1800 NU/min

Couplers with valve

25KAA Coupler, male thread BSPP
C PN
G1/4 25KAAW13MPN
G1/4 25KAAW10MPN

25KAF Coupler, hose barb
I.D. hose PN
6 25KATF06MPN
8 25KATF08MPN
10 25KATF10MPN

25KAK Coupler, Plastic Hose Connection
3/4 25KAK04MPN
3/8 25KAK05MPN
3/8 25KAK06MPN

25KAP Coupler, Push-In
C PN
4 25KAP04MPN

Plugs without valve

25SA Coupler, male thread BSPP
C PN
M5 25SFAW10MPN
G1/4 25SFAW10MPN

25SF Coupler, female thread BSPP
C PN
M5 25SF06MPN
G1/4 25SF08MPN

25SFT Plug, hose barb
I.D. hose PN
3 25SFT06MPN
4 25SFT08MPN
5 25SFT10MPN

25SK Coupler, Panel Mount with Plastic Hose Connection
3/4 25SK04MPN
3/8 25SK05MPN
3/8 25SK06MPN

25SKT Coupler, Plastic Hose Connection
3/4 25SK04MPN
3/8 25SK05MPN
3/8 25SK06MPN

25SKP Coupler, Push-In
C PN
4 25SKP04MPN

Nominal Diameter 10 mm = 80 mm²

Series 27 2400 NU/min

Couplers with valve

27KAA Coupler, male thread BSPP
C PN
G1/4 27KAAW13MPN
G1/4 27KAAW10MPN

27KAF Coupler, hose barb
I.D. hose PN
8 27KATF06MPN
10 27KATF08MPN
12 27KATF10MPN

27KAK Coupler, Plastic Hose Connection
3/4 27KAK04MPN
3/8 27KAK05MPN
3/8 27KAK06MPN

27KAP Coupler, Push-In
C PN
4 27KAP04MPN

Plugs without valve

27SA Coupler, male thread BSPP
C PN
M5 27SFAW10MPN
G1/4 27SFAW10MPN

27SF Coupler, female thread BSPP
C PN
M5 27SF06MPN
G1/4 27SF08MPN

27SFT Plug, hose barb
I.D. hose PN
3 27SFT06MPN
4 27SFT08MPN
5 27SFT10MPN

27SK Coupler, Panel Mount with Plastic Hose Connection
3/4 27SK04MPN
3/8 27SK05MPN
3/8 27SK06MPN

27SKT Coupler, Plastic Hose Connection
3/4 27SK04MPN
3/8 27SK05MPN
3/8 27SK06MPN

27SKP Coupler, Push-In
C PN
4 27SKP04MPN

BRASS/STEEL QUICK CONNECT COUPLERS - ARO PROFILE

Suitable fluids	Working pressure	Working temperature	Material
Compressed air, all fluids compatible with the material	35 bar	-20°C up to +100°C (NBR) depending on the medium	Brass / steel nickel-plated Plugs: nickel-plated steel or brass Seals: NBR

Nominal Diameter 5,5 mm = 25 mm²

Series 14 560 NU/min

Couplers with valve

14KAA Coupler, male thread BSPP
C PN
G1/4 14KAAW13MPN
G1/4 14KAAW10MPN

14KAF Coupler, hose barb
I.D. hose PN
6 14KATF06MPN
8 14KATF08MPN
10 14KATF10MPN

14KAK Coupler, Plastic Hose Connection
3/4 14KAK04MPN
3/8 14KAK05MPN
3/8 14KAK06MPN

14KAP Coupler, Push-In
C PN
4 14KAP04MPN

Plugs without valve

14SA Coupler, male thread BSPP
C PN
M5 14SFAW10MPN
G1/4 14SFAW10MPN

14SF Coupler, female thread BSPP
C PN
M5 14SF06MPN
G1/4 14SF08MPN

14SFT Plug, hose barb
I.D. hose PN
3 14SFT06MPN
4 14SFT08MPN
5 14SFT10MPN

14SK Coupler, Panel Mount with Plastic Hose Connection
3/4 14SK04MPN
3/8 14SK05MPN
3/8 14SK06MPN

14SKT Coupler, Plastic Hose Connection
3/4 14SK04MPN
3/8 14SK05MPN
3/8 14SK06MPN

14SKP Coupler, Push-In
C PN
4 14SKP04MPN

BRASS/STEEL QUICK CONNECT COUPLERS - ISO 6150 C PROFILE

Suitable fluids	Working pressure	Working temperature	Material
Compressed air, all fluids compatible with the material	35 bar	-20°C up to +100°C (NBR) depending on the medium	Brass / steel nickel-plated Plugs: nickel-plated steel Seals: NBR

Nominal Diameter 5,5 mm = 25 mm²

Series 18 970 NU/min

Couplers with valve

18KAA Coupler, male thread BSPP
C PN
G1/4 18KAAW13MPN
G1/4 18KAAW10MPN

18KAF Coupler, hose barb
I.D. hose PN
6 18KATF06MPN
8 18KATF08MPN
10 18KATF10MPN

18KAK Coupler, Plastic Hose Connection
3/4 18KAK04MPN
3/8 18KAK05MPN
3/8 18KAK06MPN

18KAP Coupler, Push-In
C PN
4 18KAP04MPN

Plugs without valve

18SA Coupler, male thread BSPP
C PN
M5 18SFAW10MPN
G1/4 18SFAW10MPN

18SF Coupler, female thread BSPP
C PN
M5 18SF06MPN
G1/4 18SF08MPN

18SFT Plug, hose barb
I.D. hose PN
3 18SFT06MPN
4 18SFT08MPN
5 18SFT10MPN

18SK Coupler, Panel Mount with Plastic Hose Connection
3/4 18SK04MPN
3/8 18SK05MPN
3/8 18SK06MPN

18SKT Coupler, Plastic Hose Connection
3/4 18SK04MPN
3/8 18SK05MPN
3/8 18SK06MPN

18SKP Coupler, Push-In
C PN
4 18SKP04MPN

Nominal Diameter 8 mm = 50 mm²

Series 84 1960 NU/min

Couplers with valve

84KAA Coupler, male thread BSPP
C PN
G1/4 84KAAW13MPN
G1/4 84KAAW10MPN

84KAF Coupler, hose barb
I.D. hose PN
8 84KATF06MPN
10 84KATF08MPN
12 84KATF10MPN

84KAK Coupler, Plastic Hose Connection
3/4 84KAK04MPN
3/8 84KAK05MPN
3/8 84KAK06MPN

84KAP Coupler, Push-In
C PN
4 84KAP04MPN

Plugs without valve

84SA Coupler, male thread BSPP
C PN
M5 84SFAW10MPN
G1/4 84SFAW10MPN

84SF Coupler, female thread BSPP
C PN
M5 84SF06MPN
G1/4 84SF08MPN

84SFT Plug, hose barb
I.D. hose PN
3 84SFT06MPN
4 84SFT08MPN
5 84SFT10MPN

84SK Coupler, Panel Mount with Plastic Hose Connection
3/4 84SK04MPN
3/8 84SK05MPN
3/8 84SK06MPN

84SKT Coupler, Plastic Hose Connection
3/4 84SK04MPN
3/8 84SK05MPN
3/8 84SK06MPN

84SKP Coupler, Push-In
C PN
4 84SKP04MPN

Nominal Diameter 5,5 mm = 25 mm²

Series 23 900 NU/min

Couplers with valve

23KAA Coupler, male thread BSPP
C PN
G1/4 23KAAW13MPN
G1/4 23KAAW10MPN

23KAF Coupler, hose barb
I.D. hose PN
6 23KATF06MPN
8 23KATF08MPN
10 23KATF10MPN

23KAK Coupler, Plastic Hose Connection
3/4 23KAK04MPN
3/8 23KAK05MPN
3/8 23KAK06MPN

23KAP Coupler, Push-In
C PN
4 23KAP04MPN

Plugs without valve

23SA Coupler, male thread BSPP
C PN
M5 23SFAW10MPN
G1/4 23SFAW10MPN

23SF Coupler, female thread BSPP
C PN
M5 23SF06MPN
G1/4 23SF08MPN

23SFT Plug, hose barb
I.D. hose PN
3 23SFT06MPN
4 23SFT08MPN
5 23SFT10MPN

23SK Coupler, Panel Mount with Plastic Hose Connection
3/4 23SK04MPN
3/8 23SK05MPN
3/8 23SK06MPN

23SKT Coupler, Plastic Hose Connection
3/4 23SK04MPN
3/8 23SK05MPN
3/8 23SK06MPN

23SKP Coupler, Push-In
C PN
4 23SKP04MPN

Nominal Diameter 8,5 mm = 60 mm²

Series 30 890 NU/min

Couplers with valve

30KAA Coupler, male thread BSPP
C PN
G1/4 30KAAW13MPN
G1/4 30KAAW10MPN

30KAF Coupler, hose barb
I.D. hose PN
8 30KATF06MPN
10 30KATF08MPN
12 30KATF10MPN

30KAK Coupler, Plastic Hose Connection
3/4 30KAK04MPN
3/8 30KAK05MPN
3/8 30KAK06MPN

30KAP Coupler, Push-In
C PN
4 30KAP04MPN

Plugs without valve

30SA Coupler, male thread BSPP
C PN
M5 30SFAW10MPN
G1/4 30SFAW10MPN

30SF Coupler, female thread BSPP
C PN
M5 30SF06MPN
G1/4 30SF08MPN

30SFT Plug, hose barb
I.D. hose PN
3 30SFT06MPN
4 30SFT08MPN
5 30SFT10MPN

30SK Coupler, Panel Mount with Plastic Hose Connection
3/4 30SK04MPN
3/8 30SK05MPN
3/8 30SK06MPN

30SKT Coupler, Plastic Hose Connection
3/4 30SK04MPN
3/8 30SK05MPN
3/8 30SK06MPN

30SKP Coupler, Push-In
C PN
4 30SKP04MPN

BRASS QUICK CONNECT COUPLERS - UK PROFILE

Nominal Diameter 5 mm = 20 mm²

Series 17 870 NU/min

Coupler with valve

17KAA Coupler, male thread BSPP
C PN
G1/4 17KAAW13MPN
G1/4 17KAAW10MPN

17KAF Coupler, hose barb
I.D. hose PN
6 17KATF06MPN
8 17KATF08MPN
10 17KATF10MPN

17KAK Coupler, Plastic Hose Connection
3/4 17KAK04MPN
3/8 17KAK05MPN
3/8 17KAK06MPN

17KAP Coupler, Push-In
C PN
4 17KAP04MPN

Plugs without valve

17SA Coupler, male thread BSPP
C PN
M5 17SFAW10MPN
G1/4 17SFAW10MPN

17SF Coupler, female thread BSPP
C PN
M5 17SF06MPN
G1/4 17SF08MPN

17SFT Plug, hose barb
I.D. hose PN
3 17SFT06MPN
4 17SFT08MPN
5 17SFT10MPN

17SK Coupler, Panel Mount with Plastic Hose Connection
3/4 17SK04MPN
3/8 17SK05MPN
3/8 17SK06MPN

17SKT Coupler, Plastic Hose Connection
3/4 17SK04MPN
3/8 17SK05MPN
3/8 17SK06MPN

17SKP Coupler, Push-In
C PN
4 17SKP04MPN

Nominal Diameter 5,5 mm = 25 mm²

Series 19 660 NU/min

Coupler with valve

19KAA Coupler, male thread BSPP
C PN
G1/4 19KAAW13MPN
G1/4 19KAAW10MPN

19KAF Coupler, hose barb
I.D. hose PN
6 19KATF06MPN
8 19KATF08MPN
10 19KATF10MPN

19KAK Coupler, Plastic Hose Connection
3/4 19KAK04MPN
3/8 19KAK05MPN
3/8 19KAK06MPN

19KAP Coupler, Push-In
C PN
4 19KAP04MPN

Plugs without valve

19SA Coupler, male thread BSPP
C PN
M5 19SFAW10MPN
G1/4 19SFAW10MPN

19SF Coupler, female thread BSPP
C PN
M5 19SF06MPN
G1/4 19SF08MPN

19SFT Plug, hose barb
I.D. hose PN
3 19SFT06MPN
4 19SFT08MPN
5 19SFT10MPN

19SK Coupler, Panel Mount with Plastic Hose Connection
3/4 19SK04MPN
3/8 19SK05MPN
3/8 19SK06MPN

19SKT Coupler, Plastic Hose Connection
3/4 19SK04MPN
3/8 19SK05MPN
3/8 19SK06MPN

19SKP Coupler, Push-In
C PN
4 19SKP04MPN

SELF-VENTING COUPLERS

Suitable fluids	Working pressure	Working temperature	Materials
Compressed air	Series KP 1600 and 1700: 12 bar C 9000: 0 to 16 bar	-20°C to +100°C (NBR)	Al: black anodized aluminium, nickel-plated brass - 1600-1700: nickel-plated brass, steel C 9000: ARO Profi zamak - ISO B and European Profile: thermoplastic

Nominal Diameter 5,5 mm = 25 mm²

Series KP - ISO C profile 810 NU/min - 2100 NU/min

Couplers with valve

5KAA Coupler, male thread BSPP
C PN
G1/4 5KAAW13MPN
G1/4 5KAAW10MPN

5KAF Coupler, hose barb
I.D. hose PN
6 5KATF06MPN
8 5KATF08MPN
10 5KATF10MPN

5KAK Coupler, Plastic Hose Connection
3/4 5KAK04MPN
3/8 5KAK05MPN
3/8 5KAK06MPN

5KAP Coupler, Push-In
C PN
4 5KAP04MPN

Plugs without valve

5SA Coupler, male thread BSPP
C PN
M5 5SFAW10MPN
G1/4 5SFAW10MPN

5SF Coupler, female thread BSPP
C PN
M5 5SF06MPN
G1/4 5SF08MPN

5SFT Plug, hose barb
I.D. hose PN
3 5SFT06MPN
4 5SFT08MPN
5 5SFT10MPN

5SK Coupler, Panel Mount with Plastic Hose Connection
3/4 5SK04MPN
3/8 5SK05MPN
3/8 5SK06MPN

5SKT Coupler, Plastic Hose Connection
3/4 5SK04MPN
3/8 5SK05MPN
3/8 5SK06MPN

5SKP Coupler, Push-In
C PN
4 5SKP04MPN

Nominal Diameter 8 mm = 50 mm²

Series KP - ISO B profile 875 NU/min - 1470 NU/min

Couplers with valve

8KAA Coupler, male thread BSPP
C PN
G1/4 8KAAW13MPN
G1/4 8KAAW10MPN

8KAF Coupler, hose barb
I.D. hose PN
8 8KATF06MPN
10 8KATF08MPN
12 8KATF10MPN

8KAK Coupler, Plastic Hose Connection
3/4 8KAK04MPN
3/8 8KAK05MPN
3/8 8KAK06MPN

8KAP Coupler, Push-In
C PN
4 8KAP04MPN

Plugs without valve

8SA Coupler, male thread BSPP
C PN
M5 8SFAW10MPN
G1/4 8SFAW10MPN

8SF Coupler, female thread BSPP
C PN
M5 8SF06MPN
G1/4 8SF08MPN

8SFT Plug, hose barb
I.D. hose PN
3 8SFT06MPN
4 8SFT08MPN
5 8SFT10MPN

8SK Coupler, Panel Mount with Plastic Hose Connection
3/4 8SK04MPN
3/8 8SK05MPN
3/8 8SK06MPN

8SKT Coupler, Plastic Hose Connection
3/4 8SK04MPN
3/8 8SK05MPN
3/8 8SK06MPN

8SKP Coupler, Push-In
C PN
4 8SKP04MPN

Nominal Diameter 7,4 mm = 43 mm²

Series KP - Euro profile 1225 NU/min

Couplers with valve

7KAA Coupler, male thread BSPP
C PN
G1/4 7KAAW13MPN
G1/4 7KAAW10MPN

7KAF Coupler, hose barb
I.D. hose PN
6 7KATF06MPN
8 7KATF08MPN
10 7KATF10MPN

7KAK Coupler, Plastic Hose Connection
3/4 7KAK04MPN
3/8 7KAK05MPN
3/8 7KAK06MPN

7KAP Coupler, Push-In
C PN
4 7KAP04MPN

Plugs without valve

7SA Coupler, male thread BSPP
C PN
M5 7SFAW10MPN
G1/4 7SFAW10MPN

7SF Coupler, female thread BSPP
C PN
M5 7SF06MPN
G1/4 7SF08MPN

7SFT Plug, hose barb
I.D. hose PN
3 7SFT06MPN
4 7SFT08MPN
5 7SFT10MPN

7SK Coupler, Panel Mount with Plastic Hose Connection
3/4 7SK04MPN
3/8 7SK05MPN
3/8 7SK06MPN

7SKT Coupler, Plastic Hose Connection
3/4 7SK04MPN
3/8 7SK05MPN
3/8 7SK06MPN

7SKP Coupler, Push-In
C PN
4 7SKP04MPN

Nominal Diameter 7,8 mm = 48 mm²

Series 1600 - Euro Profile 2083 NU/min

Couplers with valve

16KAA Coupler, male thread BSPP
C PN
G1/4 16KAAW13MPN
G1/4 16KAAW10MPN

16KAF Coupler, hose barb
I.D. hose PN
8 16KATF06MPN
10 16KATF08MPN
12 16KATF10MPN

16KAK Coupler, Plastic Hose Connection
3/4 16KAK04MPN
3/8 16KAK05MPN
3/8 16KAK06MPN

16KAP Coupler, Push-In
C PN
4 16KAP04MPN

Plugs without valve

16SA Coupler, male thread BSPP
C PN
M5 16SFAW10MPN
G1/4 16SFAW10MPN

16SF Coupler, female thread BSPP
C PN
M5 16SF06MPN
G1/4 16SF08MPN

16SFT Plug, hose barb
I.D. hose PN
3 16SFT06MPN
4 16SFT08MPN
5 16SFT10MPN

16SK Coupler, Panel Mount with Plastic Hose Connection
3/4 16SK04MPN
3/8 16SK05MPN
3/8 16SK06MPN

16SKT Coupler, Plastic Hose Connection
3/4 16SK04MPN
3/8 16SK05MPN
3/8 16SK06MPN

16SKP Coupler, Push-In
C PN
4 16SKP04MPN

Nominal Diameter 10,0 mm = 80 mm²

Series 1700 - Euro Profile 4074 NU/min

Couplers with valve

17KAA Coupler, male thread BSPP
C PN
G1/4 17KAAW13MPN
G1/4 17KAAW10MPN

17KAF Coupler, hose barb
I.D. hose PN
10 17KATF06MPN
12 17KATF08MPN
14 17KATF10MPN

17KAK Coupler, Plastic Hose Connection
3/4 17KAK04MPN
3/8 17KAK05MPN
3/8 17KAK06MPN

17KAP Coupler, Push-In
C PN