


# Plug socket with cable KMV-1-230AC-2,5

Part number: 30940

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                    | Value                                                                 |
|--------------------------------------------|-----------------------------------------------------------------------|
| Type of mounting                           | On solenoid valve via M3 central screw                                |
| Mounting position                          | optional                                                              |
| Product weight                             | 170 g                                                                 |
| Electrical connection                      | Socket<br>Type B                                                      |
| Nominal operating voltage AC               | 230 V                                                                 |
| Reverse polarity protection                | For all electrical connections                                        |
| Protective conductor connection            | Available                                                             |
| Cable length                               | 2.5 m                                                                 |
| Cable diameter                             | 6 mm                                                                  |
| Cable structure                            | 3 x 0.75 mm <sup>2</sup>                                              |
| Degree of protection                       | IP67<br>To IEC 60529                                                  |
| Ambient temperature                        | -20 °C ... 80 °C                                                      |
| CE mark (see declaration of conformity)    | To EU Low Voltage Directive<br>In accordance with EU RoHS Directive   |
| CE marking (see declaration of conformity) | To UK RoHS instructions<br>To UK regulations for electrical equipment |
| LABS (PWIS) conformity                     | VDMA24364-B2-L                                                        |
| Corrosion resistance class CRC             | 1 - Low corrosion stress                                              |
| Material cable sheath                      | PVC                                                                   |
| Material housing                           | PC                                                                    |
| Material electrical contact                | Bronze                                                                |