

# Trunnion flange CRZNG-125

Part number: 185362

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                            | Value                                                                                                                                                                                                                  |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                               | 125                                                                                                                                                                                                                    |
| Based on standard                                  | ISO 15552                                                                                                                                                                                                              |
| Corrosion resistance class CRC                     | 4 - Very high corrosion stress                                                                                                                                                                                         |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                                                                                                                                                                         |
| Suitability for the production of Li-ion batteries | Metals with more than 5% copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Ambient temperature                                | -40 °C ... 150 °C                                                                                                                                                                                                      |
| Product weight                                     | 3484 g                                                                                                                                                                                                                 |
| Note on materials                                  | RoHS-compliant                                                                                                                                                                                                         |
| Material mounting                                  | High-alloy stainless steel                                                                                                                                                                                             |
| Material screws                                    | High-alloy stainless steel                                                                                                                                                                                             |