



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 385AX, Tapered Roller Bearings - Single Cones - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	385
Cone Part Number	385AX
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions)¹	42200 lbf 188000 N
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions)²	10900 lbf 48700 N



Dimensions

d - Cone Bore	2 in 50.8 mm
B - Cone Width	0.8640 in 21.946 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius³	0.03 in 0.8 mm
da - Cone Frontface Backing Diameter	2.28 in 58 mm
db - Cone Backface Backing Diameter	2.28 in 58 mm
Ab - Cage-Cone Frontface Clearance	0.11 in 2.8 mm
Aa - Cage-Cone Backface Clearance	0.03 in 0.8 mm
a - Effective Center Location⁴	-0.12 in -3 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁵	6280 lbf 28000 N
C1 - Dynamic Radial Rating (1 million revolutions)⁶	24200 lbf 108000 N
C0 - Static Radial Rating	24100 lbf 107000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁷	3810 lbf 16900 N

Factors

K - Factor⁸	1.65
G1 - Heat Generation Factor (Roller-Raceway)	42
G2 - Heat Generation Factor (Rib-Roller End)	15.7
Cg - Geometry Factor⁹	0.0859

¹ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

² Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

³ These maximum fillet radii will be cleared by the bearing corners.

⁴ Negative value indicates effective center inside cone backface.


⁵ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁶ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁷ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ Geometry constant for Lubrication Life Adjustment Factor a_3 .



IMPERIAL UNITS

Number of Rollers Per Row19	TIMKEN® THE TIMKEN COMPANY NORTH CANTON, OHIO USA	385AX Tapered Roller Bearings - Single Cones - Imperial K Factor1.65 Dynamic Radial Rating - C906280lbf Dynamic Thrust Rating - Ca903810lbf Dynamic Radial Rating - C124200lbf
Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.		FOR DISCUSSION ONLY