

7 DRAWER PREMIUM ROLLER CABINET

Description

Premium 7 drawer roller cabinet with integrated work surface of anti-slip black ribbed rubber

Central locking by key lock

Ergonomic fibre-filled nylon handle for high strength

Rolling: made of steel with rubber shrouding, Ø 125 mm and width 32 mm, 2 fixed casters, 1 single directional castor and 1 directional castor with full brake.

Drawers:

- 100% opening
- Permissible load per drawer 30kg

Anti-tilt safety system.

- Dimensions:

- 3 drawers: W 540 x D 410 x H 65 mm
- 3 drawers: W 540 x P 410 x H 105 mm
- 1 drawer: W 540 x D 410 x H 189 mm

Mobility load capacity 500 kg

Static load capacity 900 kg

Dimensions : W 721 x D 494 x H 1010 mm

Weight 72,5kg

RAL Colours 9005 and 9007



In addition, a range of equipped foams that fit perfectly with our ROEBUCK roller cabinets are available for sale:

1/3 dimensions (180 x 410 x 30mm)

- Sku 890399 9 open ended spanners
- Sku 890408 7 combination spanners AF
- Sku 890411 7 open ended spanners
- Sku 890402 12 combination ratchet spanners
- Sku 890405 3, 4 in 1 ratchet ring spanners
- Sku 890414 6 slot and phillips screwdriver
- Sku 890417 6 slot and pozidriv screwdrivers
- Sku 890423 4 pliers
- Sku 890420 6 VDE 1000V screwdrivers
- Sku 890429 4 VDE 1000V pliers
- Sku 890447 ¼ ratchets and sockets - 48 elements
- Sku 890450 ½ ratchets and sockets - 22 elements

2/3 dimensions (360 x 410 x 30mm)

- Sku 890393 12 combination spanners
- Sku 890396 9 double ended ring spanners
- Sku 890426 6 circlips pliers
- Sku 890432 6 files

3/3 dimensions (540 x 410 x 30mm)

- Sku 890435 ratchets and sockets – 78 elements
- Sku 890438 pliers and strike hammer – 27 elements
- Sku 890441 pliers and ball hammer – 27 elements
- Sku 890444 spanners and screwdrivers – 25 elements

Applications

These tool trolleys are perfect for use in workshops, warehouses and general maintenance

Strong points

Anti-tilt safety system

Characteristics

Brand Ref.	MDM	Colour	Draw number	Dimensions mm	Permissible load kg
865487	9244322	GREY	7.0	721x494x1010	900