


**GE25-XL-KRR-B**

Radial insert ball bearing

Radial insert ball bearing GE...XL-KRR-B

X-life

Technical information



Your current product variant

Sealing	KRR	Lip seals on both sides
Shape of outer surface	B	

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D SP	52 mm	Outside diameter
B	34.9 mm	Width
C ur	370 N	Fatigue load limit, radial
B 1	44.5 mm	Locking collar total width
C r	14,900 N	Basic dynamic load rating, radial
C 0r	7,800 N	Basic static load rating, radial
m	246.13 g	Weight










Dimensions

C	15 mm	Width, outer ring
C 2	16.7 mm	Sealing total width
S	17.5 mm	Distance raceway
d 1	33.8 mm	Rib diameter inner ring
D 1	42.5 mm	Outside diameter seal
C a	4.1 mm	Distance to lubrication hole
d 3	37.5 mm	Outside diameter locking collar/locknut
W	3 mm	Width of flats

Calculation factors

f 0	13.8	Calculation factor
-----	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides
	Static angular error and misalignment