



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 396, Tapered Roller Bearings - Single Cones - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	395
Cone Part Number	396
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions)¹	38700 lbf 172000 N
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions)²	10000 lbf 44600 N



Dimensions

d - Cone Bore	1.9685 in 50 mm
B - Cone Width	0.8660 in 21.996 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius³	0.03 in 0.8 mm
da - Cone Frontface Backing Diameter	2.36 in 60 mm
db - Cone Backface Backing Diameter	2.4 in 61 mm
Ab - Cage-Cone Frontface Clearance	0.11 in 2.8 mm
Aa - Cage-Cone Backface Clearance	0.05 in 1.3 mm
a - Effective Center Location⁴	-0.03 in -0.8 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁵	5760 lbf 25600 N
C1 - Dynamic Radial Rating (1 million revolutions)⁶	22200 lbf 98900 N
C0 - Static Radial Rating	28100 lbf 125000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁷	3970 lbf 17600 N

Factors

K - Factor⁸	1.45
G1 - Heat Generation Factor (Roller-Raceway)	56
G2 - Heat Generation Factor (Rib-Roller End)	21.4
Cg - Geometry Factor⁹	0.0984

¹ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

² Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

³ These maximum fillet radii will be cleared by the bearing corners.

⁴ Negative value indicates effective center inside cone backface.


⁵ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁶ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁷ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ Geometry constant for Lubrication Life Adjustment Factor a_3 .



IMPERIAL UNITS

Number of Rollers Per Row22	<div>TIMKEN®</div>	396 Tapered Roller Bearings - Single Cones - Imperial	
	<div>THE TIMKEN COMPANY NORTH CANTON, OHIO USA</div>	<div>K Factor1.45</div> <div>Dynamic Radial Rating - C905760lbf</div> <div>Dynamic Thrust Rating - Ca903970lbf</div> <div>Dynamic Radial Rating - C122200lbf</div>	
Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.		FOR DISCUSSION ONLY	