

## Rolling bearing greases

### ARCANOL-SPEED2,6-250G (Series ARCANOL-SPEED2,6)

Special greases for high speed applications at high speeds and low loads

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

	Base oil type: synthetic oil	
	25 mm <sup>2</sup> / s	Base oil viscosity at 40°C
	6 mm <sup>2</sup> / s	Base oil viscosity at 100°C
	-40 .. +120 °C	Operating temperature range
	80 °C	Continuous limit temperature
	Thickener type: Lithium complex soap	
	2-3	Consistency (NLGI class)
	0,94 kg / dm <sup>3</sup>	Density
	2000000 mm/min	Speed limit n*dm Ball bearings, cylindrical roller bearings

	200000 mm/min	Speed limit $n \cdot dm$ Other roller bearings (not for axial cylindrical roller bearings and axial spherical roller bearings)
	0,25 kg	Container size
		Container type: tube

