

Plummer block housing units PSHE35-TV-FA125.5 (Series PSHE..-TV-FA125)

plastic housing, radial insert ball bearing with eccentric locking collar, with Corrotect coating, P seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	35 mm
L	110 mm
H ₂	95 mm
A	47,5 mm
B ₁	39 mm
d _{3 max}	51 mm
H	47,6 mm
J	82,6 mm
K	M10
Q	1/4 - 28 UNF

S ₁	29,5 mm	
m	0,8 kg	Mass
C _r	27500 N	Basic dynamic load rating, radial
C _{0r}	15300 N	Basic static load rating, radial
C _{0r G}	8000 N	Load carrying capacity of housing, radial
	GEH.SHE07-TV	Designation of housing
	GRAE35-NPP-B-FA107/125.5	Designation of bearing
	KASK07-S-G	Bearing end cap, closed design. Each housing unit is supplied with an end cap.
	KASK07-S-R-NBR	Bearing end caps for housing units, open design, with integral rotary shaft seal. Available by agreement.

