


HMK4

Union

60° Cone / 60° Cone

Mates with 92, B1, B2 and B4 style hose fitting



TUBE FITTING PART #	END SIZE		C HEX (mm)	D1 DRILL (mm)	D2 DRILL (mm)	L (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)
	1 BSPP	2 BSPP					S
2HMK4	1/8	1/8	14	3.5	3.5	23.5	5.1
4-2HMK4	1/4	1/8	19	4.7	3.5	28.0	5.1
4HMK4	1/4	1/4	19	4.7	4.7	31.5	5.1
6-4HMK4	3/8	1/4	22	7.9	4.7	33.2	5.1
6HMK4	3/8	3/8	22	7.9	7.9	34.7	2.9
8-4HMK4	1/2	1/4	27	11.1	4.7	36.7	2.9
8-6HMK4	1/2	3/8	27	11.1	7.9	38.2	2.9
8HMK4	1/2	1/2	27	11.1	11.1	40.7	2.9
10-8HMK4	5/8	1/2	30	14.3	11.1	43.2	2.9
10HMK4	5/8	5/8	30	14.3	14.3	45.2	2.9
12-4HMK4	3/4	1/4	32	16.7	4.7	39.2	2.9
12-6HMK4	3/4	3/8	32	16.7	7.9	40.7	2.9
12-8HMK4	3/4	1/2	32	16.7	11.1	43.2	2.9
12-10HMK4	3/4	5/8	32	16.7	14.3	45.2	2.9
12HMK4	3/4	3/4	32	16.7	16.7	45.2	2.9
16-8HMK4	1	1/2	41	22.2	11.1	46.9	1.7
16-10HMK4	1	5/8	41	22.2	14.3	48.9	1.7
16-12HMK4	1	3/4	41	22.2	16.7	48.9	1.7
16HMK4	1	1	41	22.2	22.2	51.9	1.7
20-12HMK4	1 1/4	3/4	50	28.6	16.7	57.4	1.5
20-16HMK4	1 1/4	1	50	28.6	22.2	60.4	1.5
20HMK4	1 1/4	1 1/4	50	28.6	28.6	61.4	1.5
24-16HMK4	1 1/2	1	55	33.3	22.2	64.4	1.5
24-20HMK4	1 1/2	1 1/4	55	33.3	28.6	65.4	1.5
24HMK4	1 1/2	1 1/2	55	33.3	33.3	67.4	1.5
32-24HMK4	2	1 1/2	70	46.0	33.3	72.9	1
32HMK4	2	2	70	46.0	46.0	76.4	1

Dimensions and pressures for reference only, subject to change.