

TYGRIS TECHNICAL DATA SHEET

Industrial Maintenance Aerosols

Chain & Wire Rope Lubricant

CODE: **R220**

Lubricates and extends the life of chains and wire ropes

A heavy duty, molybdenum disulphide reinforced lubricant which penetrates deeply into drive chains and wire ropes to give long lasting lubrication, preventing corrosion, wear and chain elongation. It gives outstanding performance under extreme load and is resistant to fling off.

Benefits:	Use on chain blocks, drive chains, fork lift chains and wire ropes Extreme pressure additives for heavy loads Excellent lubrication properties Resistant to flinging off Penetrates deeply Only a thin film is left on the surface for corrosion prevention High resistance to wash off
-----------	---

Technical Data:

Appearance:	Brown foaming spray
Odour:	Oily solvent
Contents:	Blend of mineral oils, molybdenum disulphide, bitumen, xylene, white spirit, extreme pressure and dewatering additives, solvent and hydrocarbon propellants. No silicones
Storage:	Below 50°C
Flash Point:	<0°C
Temperature range:	-10° to 180°C
Relative Density:	0.845
Solubility:	Insoluble in water
Pack Sizes:	12 x 400ml cans
Directions for Use:	Shake can well before use. Spray onto surface to be treated from 15-30cm, allow to penetrate and wipe off excess with a cloth. After use, invert can and spray to clear nozzle.

