



Technical data

32220U

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Visual(s)



Product definition

d	100 mm
D	180 mm
B	46 mm
C	39 mm
T	49 mm
d1	137.5 mm
a	41.5 mm
rs min	3 mm
r1s min	2.5 mm
e	0.42
Y2	1.43
Y0	0.79
Mass	5.12 kg
ISO 355 reference	T3FC100
Brand	NTN

Product performance

Dynamic load, C	330 kN
Rating life coefficient, A2	1
Static load, C0	465 kN
Fatigue limit load, Cu	51.4 kN
Nlim (oil)	2,700 Tr/min
Nlim (grease)	2,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.63 Hz
Characteristic outer ring frequency, BPF0	8.58 Hz
Characteristic inner ring frequency, BPFI	11.42 Hz

Abutment dimensions

da max	114 mm
db min	114 mm
Da min	154 mm
Da max	168 mm
Db min	171 mm
Ca min	5 mm
Cb min	10 mm
ra max	2.5 mm
r1a max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table