


EW-R-ED

Assembled Adjustable Swivel Elbow
24° Flareless / BSPP with EOlastic Seal



TUBE FITTING PART #	END SIZE		d3 (mm)	i (mm)	I 1 (mm)	L1 (mm)	L2 (mm)	S1 (mm)	S2 (mm)	S3 (mm)	STANDARD Pressure Rating (bar)				
	1	2									EO		EO-2		
	(mm)	BSPP									CF	71	MS	CF	71
EW06LRED	6	G 1/8 A	14	8	12.0	27	34.5	14	14	12	315			315	
EW08LRED	8	G 1/4 A	19	12	14.0	29	37.5	19	17	12	315			315	
EW10LRED	10	G 1/4 A	19	12	15.0	30	40.0	19	19	14	315			315	
EW12LRED	12	G 3/8 A	22	12	17.0	32	42.0	22	22	17	315			315	
EW15LRED	15	G 1/2 A	27	14	21.0	36	46.5	27	27	19	315			315	
EW18LRED	18	G 1/2 A	27	14	23.5	40	50.0	27	32	24	315			315	
EW22LRED	22	G 3/4 A	32	16	27.5	44	55.0	32	36	27	160			160	
EW28LRED	28	G 1 A	40	18	30.5	47	59.0	41	41	36	160			160	
EW35LRED	35	G 1 1/4 A	50	20	34.5	56	68.5	50	50	41	160				
EW42LRED	42	G 1 1/2 A	55	22	40.0	63	75.0	55	60	50	160				
EW06SRED	6	G 1/4 A	19	12	16.0	31	40.0	19	17	12	630			630	
EW08SRED	8	G 1/4 A	19	12	17.0	32	42.5	19	19	14	630			630	
EW10SRED	10	G 3/8 A	22	12	17.5	34	45.0	22	22	17	630			630	
EW12SRED	12	G 3/8 A	22	12	21.5	38	48.0	22	24	17	630				
EW14SRED	14	G 1/2 A	27	14	22.0	40	54.0	27	27	19	630				
EW16SRED	16	G 1/2 A	27	14	24.5	43	55.0	27	30	24	400			400	
EW20SRED	20	G 3/4 A	32	16	26.5	48	65.0	32	36	27	400			400	
EW25SRED	25	G 1 A	40	18	30.0	54	73.0	41	46	36	400			400	
EW30SRED	30	G 1 1/4 A	50	20	35.5	62	78.5	50	50	41	400			400	
EW38SRED	38	G 1 1/2 A	55	22	41.0	72	89.0	55	60	50	315			315	

For EO-2 part number, insert "Z" between size and pressure series.

Example: EW06ZLREDCF

Dimensions and pressures for reference only, subject to change.



Parker Hannifin Corporation
Tube Fittings Division
Columbus, Ohio
<http://www.parker.com/tfd>