




Technical datasheet

NJ2309EG1

Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, brass cage.

Visual(s)



Product definition

d	45 mm
D	100 mm
B	36 mm
E	88.5 mm
F	58.5 mm
d1	64.5 mm
rs min	1.5 mm
r1s min	1.5 mm
Radial clearance class	CN
Mass (without HJ ring)	1.42 kg
Brand	NTN

Product performance

Dynamic load, C	137 kN
Static load, C0	153 kN
Fatigue limit load, Cu	18.7 kN
Nlim (oil)	6,800 rpm
Nlim (grease)	5,700 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.7 Hz
Characteristic outer ring frequency, BPF0	5.17 Hz
Characteristic inner ring frequency, BPFI	7.83 Hz

Abutment dimensions

da min	53 mm
da max	57 mm
dc min	66 mm
Da max	92 mm
ra max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$Po = Fr$$