

## Rolling bearing greases

### ARCANOL-TEMP110-400G (Series ARCANOL-TEMP110)

High temperature greases for applications with continuous limit temperature of up to +110°C

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

	Base oil type: partially synthetic Oil	
	130 mm <sup>2</sup> / s	Base oil viscosity at 40°C
	14 mm <sup>2</sup> / s	Base oil viscosity at 100°C
	-35 .. +160 °C	Operating temperature range
	110 °C	Continuous limit temperature
	Thickener type: Lithium complex soap	
	2	Consistency (NLGI class)
	0,90 kg / dm <sup>3</sup>	Density
	500000 mm/min	Speed limit n*dm

	Ball bearings, cylindrical roller bearings	
	250000 mm/min	Speed limit $n \cdot d_m$ Other roller bearings (not for axial cylindrical roller bearings and axial spherical roller bearings)
	0,4 kg	Container size
	Container type: cartridge	

