


GE-R

Male Connector
24° Flareless / BSPP

[CLICK HERE
to go to
GE-R L-Series](#)

S-Series

Cutting face DIN 3852, form B, G
(BSPP) thread

TUBE FITTING PART #	END SIZE		d3 (mm)	i (mm)	l1 (mm)	L1 (mm)	S1 (mm)	S2 (mm)	STANDARD Pressure Rating (bar)		
	1 (mm)	2 BSPP							EO		
									CF	71	MS
GE06SR	6	G 1/4 A	18	12	13.0	28	19	17	400		250
GE06SR1/2	6	G 1/2 A	26	14	18.0	33	27	17	400		
GE08SR	8	G 1/4 A	18	12	15.0	30	19	19	400	400	250
GE08SR3/8	8	G 3/8 A	22	12	15.5	30	22	19	400		
GE10SR	10	G 3/8 A	22	12	15.0	31	22	22	400	400	250
GE10SR1/4	10	G 1/4 A	18	12	14.5	31	19	22	400		
GE10SR1/2	10	G 1/2 A	26	14	17.5	34	27	22	400	400	
GE12SR	12	G 3/8 A	22	12	17.0	33	22	24	400	400	250
GE12SR1/4	12	G 1/4 A	18	12	16.5	33	22	24	400	400	
GE12SR1/2	12	G 1/2 A	26	14	17.5	34	27	24	400	400	
GE14SR	14	G 1/2 A	26	14	19.0	37	27	27	400		250
GE14SR3/8	14	G 3/8 A	22	12	18.5	36	24	27	400		
GE16SR	16	G 1/2 A	26	14	18.5	37	27	30	400	400	250
GE16SR3/8	16	G 3/8 A	22	12	18.0	36	27	30	400	400	
GE16SR3/4	16	G 3/4 A	32	16	20.5	39	32	30	400		
GE20SR	20	G 3/4 A	32	16	20.5	42	32	36	400	400	250
GE20SR1/2	20	G 1/2 A	26	14	20.5	42	32	36	400	400	
GE25SR	25	G 1 A	39	18	23.0	47	41	46	250		160
GE25SR3/4	25	G 3/4 A	32	16	23.0	47	41	46	250		
GE30SR	30	G 1 1/4 A	49	20	23.5	50	50	50	160		100
GE30SR1	30	G 1 A	39	18	23.5	50	46	50	160	160	
GE38SR	38	G 1 1/2 A	55	22	26.0	57	55	60	160		100
GE38SR11/4	38	G 1 1/4 A	49	20	26.0	57	55	60	160		

Dimensions and pressures for reference only, subject to change.



Parker Hannifin Corporation
Tube Fittings Division
Columbus, Ohio
<http://www.parker.com/tfd>