

## Rolling bearing greases

### ARCANOL-TEMP90-1KG (Series ARCANOL-TEMP90)

High temperature greases for applications with continuous limit temperature of up to +90°C

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

	Base oil type: mineral oil
148 mm <sup>2</sup> / s	Base oil viscosity at 40°C
15,5 mm <sup>2</sup> / s	Base oil viscosity at 100°C
-40 .. +160 °C	Operating temperature range
90 °C	Continuous limit temperature
	Thickener type: Polycarbamide
3	Consistency (NLGI class)
0,90 kg / dm <sup>3</sup>	Density
700000 mm/min	Speed limit n*dm

		Ball bearings, cylindrical roller bearings
250000 mm/min	Speed limit n*dm Other roller bearings (not for axial cylindrical roller bearings and axial spherical roller bearings)	
1 kg	Container size	
	Container type: can	

