

TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION



F600 Series - VERTICAL FOLD FLAT DISPOSABLE DUST MASK

F600 SERIES F622 - Box of 30 - FFP2V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK / BGW170-000-S00



DESCRIPTION

Disposable vertical fold flat mask with mouldable nose bridge and foam pad on the inside for comfort and a firmer fit.

OPTIONS

F600 SERIES F621 - Retail Box of 15 x 2 pack masks - FFP2 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGV120-000-T00)

F600 SERIES F621 - Box of 40 - FFP2 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGV120-000-Q00)

F600 SERIES F622 - Retail Box of 10 x 2 pack masks - FFP2V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGW170-000-T00)

F600 SERIES F622 - Box of 30 - FFP2V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGW170-000-S00)

F600 SERIES F631 - Box 40 - FFP3 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGX130-000-Q00)

F600 SERIES F632 - Retail Box of 10 x 2 pack masks - FFP3V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGR180-000-T00)

F600 SERIES F632 - Box of 30 - FFP3V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGR180-000-S00)

SAFETY STANDARDS

EN 149



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 20 Apr 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Classification
FFP2 (Filtering Facepiece Particulate - Valved)

Usage
NR (Non-Reusable)

Minimum Filtration Efficiency
94% For FFP2 Rated

Nominal Protection Factor
12

Mask Design
Vertical Fold Flat

Toggle Harness adjustment system
Yes

Mask Material
Polypropylene



Product Weight
10g (Approx) Each Mask

Individually Wrapped
Yes



Filter Type
P (Protects Against Solid and Liquid Aerosols)



Activated Carbon Layer
No

Maximum Total Inward Leakage (TIL)
8%

UK Assigned Protection Factor
10



Exhalation Valve
Yes - Polystyrene exhalation valve with rubber diaphragm




Nose Bridge
Moulded in mask

Filter Shelf Life
5 Years

Latex free
Yes

FEATURES



Foam Padded Nose Bridge

A mouldable nose bridge and foam pad on the inside for comfort and a firmer fit.



Folds Flat

Fold flat design is compact and easy to carry in a pocket.



Toggle Adjustment

Toggle adjuster on each strap to achieve an effective facial fit.



Exhalation Valve

Low resistance exhalation valve for easy breathing.

RANGE

F600
SERIES

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [Declaration of Conformity \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 20 Apr 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.

