
Flush mounted boxes for use within stud walls for alleviating the necessity of using noggins. Boxes feature a wide securing flange around the outer rim.

Product information

- Wide securing flange to prevent box passing through cavity
- Swivelling snap out clamps will tightly grip a range of standard thickness building boards
- Earth terminal provision incorporated
- British Patent Application No. 8208041

Standard colour
WH
WH : White



Wall thickness adjustment	Clamp colour
1 - 9mm	Grey
6 - 14mm	White
18 - 25mm	Green
9 - 26mm	Black



Wide securing flanges





1 gang 34mm internal depth			
code	adjustment	pack	
MDLB3WH	1-9mm	20	
MDLB1WH	6-14mm	20	
MDLB7WH	18-25mm	20	



34mm internal depth

5-mini internar acptir			
code	adjustment	pack	
MDLB4WH	1-9mm	10	
MDLB2WH	6-14mm	10	
MDLB8WH	18-25mm	10	



Dual gang 34mm internal depth

code	adjustment	pack
MDLB20WH	1-9mm	5
MDLB22WH	6-14mm	5
MDLB24WH	18-25mm	5



1 gang

25mm internal depth			
code	adjustment	pack	
MDLB13WH	1-9mm	10	



2 gang 25mm internal depth

code	adjustment	pack
MDLB14WH	1-9mm	10



Intumescent fire barrier pads

Fire Barrier Pads are now a requirement of Document B of the UK Building Regulations. For information on Fire Barrier Pads please refer to page 237 in our Fire and Security section or contact our Technical Team on +44 (0)1424 856688.





MDLB29WH	9-26mm	10	
code	adjustment	pack	
40mm internal depth			



2 gang

46mm internal depth			
code	pack		
MDLB30WH	9-26mm	5	





Brass earthing terminal

code	Rating	pack
MET1	15 Amp	100



Acoustic hoods

ricoustic Hoods			
code	description	pack	
MDLA1	1 gang	10	
MDLA2	2 gang	10	