31.01.2023, 13:45:04 IST SCHAEFFLER




RTUE65-214-XL


Take-up housing unit

Schaeffler ID: 0008775300000

Take-up housing units RTUE, cast iron housing, radial insert ball bearing with eccentric locking collar, R seals

Technical information





Main Dimensions & Performance Data

| d | 65 mm | Bore diameter |
|---|---------|---------------|
| Н | 166 mm | Height |
| L | 214 mm | Length total |
| | 7.11 kg | Weight |

Mounting dimensions

| A ₁ | 25 mm | Width guidance groove |
|----------------|----------|--|
| | H13 | Width guidance groove clearance |
| H ₁ | 151 mm | Distance guidance grooves |
| | 0.25 mm | Upper distance guidance groove tolerance |
| | -0.25 mm | Lower distance guidance groove tolerance |
| N | 41 mm | Fixing bore |

Dimensions

| L ₁ | 135 mm | Distance shaft axis |
|----------------|---------|---------------------------------------|
| L ₂ | 20 mm | Length fixed link |
| L ₃ | 120 mm | Length guidance groove |
| А | 70 mm | Width housing fixing side |
| N ₁ | 35 mm | Width recess |
| N ₂ | 70 mm | Height recess |
| S ₁ | 44.5 mm | Distance of raceway to locking collar |
| Т | 110 mm | Height housing fixing side |
| Q | M6 | Connection thread for lubrication |
| A ₂ | 50 mm | Width housing |

Additional information

| TUE13/14 | Housing |
|-------------------|---------------------|
| GE65-214-XL-KRR-B | Bearing designation |

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.

31.01.2023, 13:45:04 IST SCHAEFFLER

Temperature range

| T _{min} | -20 °C | Operating temperature min. |
|------------------|--------|----------------------------|
| T _{max} | 120 °C | Operating temperature max. |