



# Straight Mobile Connector - IP44

- Designed for ease of assembly and wiring.
- Twist grip cable gland locking system for quick mounting.
- Rated current from 16A up to 32A.
- IK08 rating as per IEC/EN 62262.
- Rated voltage option from 110V up to 400V.
- Thermoplastic grip material.



## PM16/2800FPB

### Straight connector

| TECHNICAL DATA          |                                  | REGISTRY                  |                   |
|-------------------------|----------------------------------|---------------------------|-------------------|
| Rated current           | 16A                              | Net weight                | 0.21KG            |
| Frequency               | 50/60Hz                          | Gross Weight              | 0.24KG            |
| Poles                   | 3P+N+ $\frac{PE}{\text{ground}}$ | EAN Code                  | 8014950031573     |
| Clock Position          | 6h                               | Min order quantity        | 1                 |
| Protection degree       | IP44                             | REFERENCE STANDARDS       |                   |
| Rated operating voltage | 400V                             | STANDARDS                 |                   |
| Manufacturing material  | Thermoplastic                    | EN 60309-1:1999/A1:2007   | 2014/35/EU (LVD)  |
|                         |                                  | EN 60309-1:1999/A2:2012   | 2011/65/EU (RoHS) |
|                         |                                  | EN 63000:2018             | 2012/19/EU (WEEE) |
|                         |                                  | EN 60309-2:1999/A2:2012   |                   |
|                         |                                  | EN 60309-2:1999/A1:2007   |                   |
|                         |                                  | EN 60309-1:1999           |                   |
|                         |                                  | EN 60309-1:1999/A1AC:2014 |                   |
|                         |                                  | EN 60309-2:1999           |                   |