

FLOODLIGHT PIR

LED Floodlight



Features:

Ideal for retro-fit of existing halogen fixtures

Available in 7 different outputs

High quality toughened safety glass

Ideal for lighting buildings, car parks or doorways

Weatherproof IP65 construction

Available without PIR

Choice of black or white body

Supplied with stirrup and 1.0m of flex for column, bracket or surface fix

35,000 hours lifetime (L70/B50)

Construction:

Up to 102 lumens per watt efficacy



FLOODLIGHT PIR

LED Floodlight

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCSF10NWP	10W LED Floodlight - 4000K	800	10	80	0.52
XCSF20NWP	20W LED Floodlight - 4000K	1600	20	80	1.01
XCSF30NWP	30W LED Floodlight - 4000K	2700	30	90	1.61
XCSF50NWP	50W LED Floodlight - 4000K	4700	50	94	2.40
XCSF100NW	100W LED Floodlight - 4000K	9500	100	95	4.74
XCSF150NWP	150W LED Floodlight - 4000K	15300	150	102	5.34
XCSF200NWP	200W LED Floodlight - 4000K	19400	200	97	5.45
XCSF10WWP	10W LED Floodlight - 3000K	700	10	70	0.52
XCSF20WWP	20W LED Floodlight - 3000K	1400	20	70	1.01
XCSF30WWP	30W LED Floodlight - 3000K	2400	30	80	1.61
XCSF50WWP	50W LED Floodlight - 3000K	4100	50	82	2.40
XCSF100WWP	100W LED Floodlight - 3000K	8300	80	83	4.74
XCSF150WWP	150W LED Floodlight - 3000K	13400	120	90	5.34
XCSF200WWP	200W LED Floodlight - 3000K	17000	160	85	5.45

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCSF10NWP	130	110	40
XCSF20NWP	180	150	50
XCSF30NWP	225	190	60
XCSF50NWP	280	235	70
XCSF100NW	370	310	90
XCSF150NWP	425	325	100
XCSF200NWP	425	325	100
XCSF10WWP	130	110	40
XCSF20WWP	180	150	50
XCSF30WWP	225	190	60
XCSF50WWP	280	235	70
XCSF100WWP	370	310	90
XCSF150WWP	425	325	100
XCSF200WWP	425	325	100

