


C4OMX

Male Elbow – BSPP
37° Flare / BSPP-ORR



Y* – Across wrench flats

TUBE FITTING PART #	END SIZE			T TUBE END UN/UNF-2A	C4 (mm)	D (mm)	D2 (mm)	M (mm)	M7 (mm)	Y (mm)	Dynamic Pressure (x 1,000 PSI)		
	1		2								S	SS	B
	(mm)	(in.)	BSPP										
4C4OMX	6	1/4	1/8 - 28	7/16 - 20	14	4.4	4.4	22.6	26.5	11	3.6	3.6	2.3
4-4C4OMX	6	1/4	1/4 - 19	7/16 - 20	19	4.4	7.5	26.9	32.0	14	3.6	2.9	1.9
5C4OMX	8	5/16	1/8 - 28	1/2 - 20	14	6.0	4.4	24.1	27.0	13	3.6	3.6	2.3
5-4C4OMX	8	5/16	1/4 - 19	1/2 - 20	19	6.0	7.5	26.6	32.0	14	3.6	2.9	1.9
5-6C4OMX	8	5/16	3/8 - 19	1/2 - 20	22	6.0	9.9	28.5	37.0	19	3.6	2.9	1.9
6C4OMX	10	3/8	1/4 - 19	9/16 - 18	19	7.5	7.5	26.9	32.0	14	3.6	2.9	1.9
6-6C4OMX	10	3/8	3/8 - 19	9/16 - 18	22	7.5	9.9	29.0	37.0	19	3.6	2.9	1.9
8-4C4OMX	12	1/2	1/4 - 19	3/4 - 16	19	9.9	7.5	31.8	37.0	19	3.6	2.9	1.9
8C4OMX	12	1/2	3/8 - 19	3/4 - 16	22	9.9	9.9	31.8	37.0	19	3.6	2.9	1.9
8-8C4OMX	12	1/2	1/2 - 14	3/4 - 16	27	9.9	12.3	33.8	43.0	22	3.6	2.9	1.9
10-6C4OMX	16	5/8	3/8 - 19	7/8 - 14	22	12.3	9.9	36.8	36.0	22	3.6	2.9	1.9
10C4OMX	14,15,16	5/8	1/2 - 14	7/8 - 14	27	12.3	12.3	36.8	43.0	22	3.6	2.9	1.9
10-12C4OMX	15	5/8	3/4 - 14	7/8 - 14	36	12.3	15.5	39.2	49.5	27	3.6	2.9	1.9
12-8C4OMX	18,20	3/4	1/2 - 14	1 1/16 - 12	27	15.5	12.3	42.2	49.5	27	3.6	2.9	1.9
12C4OMX	18,20	3/4	3/4 - 14	1 1/16 - 12	36	15.5	15.5	42.2	49.5	27	3.6	2.9	1.9
12-16C4OMX	18	3/4	1 - 11	1 1/16 - 12	41	15.5	21.5	44.7	52.0	33	3.6	2.9	1.9
16-12C4OMX	25	1	3/4 - 14	1 5/16 - 12	36	21.5	15.5	46.0	47.0	33	3.6	2.9	1.9
16C4OMX	25	1	1 - 11	1 5/16 - 12	41	21.5	21.5	46.0	52.0	33	3.6	2.9	1.9
20-16C4OMX	30,32	1 1/4	1 - 11	1 5/8 - 12	41	27.5	21.5	52.3	57.0	41	3.6	2.3	1.5
20C4OMX	30,32	1 1/4	1 1/4 - 11	1 5/8 - 12	50	27.5	27.5	52.3	57.0	41	3.0	2.3	1.5
24-20C4OMX	38	1 1/2	1 1/4 - 11	1 7/8 - 12	50	33.0	27.5	59.2	60.5	48	3.0	2.0	1.3
24C4OMX	38	1 1/2	1 1/2 - 11	1 7/8 - 12	55	33.0	33.0	59.2	60.5	48	2.0	2.0	1.3

Dimensions and pressures for reference only, subject to change.