


Datasheet

Dimensions



[1] Retaining nut

[2] Solenoid coil
(can be rotated 360° on the armature)





[3] Plug pins



Note
Can only be used on aluminium valves with valve body dimensions ≥ 26 x 16 x 14 mm

Download CAD data → www.festo.com

Type	B1	H1	H2	L1	L2
MSFG-...	22	29	33.8	29.5	12.5
MSFW-...					

Ordering data					
	Description	LABS (PWIS) conformity	Operating voltage	Part no.	Type
Solenoid coil, plug to industry standard, type B					
	Without plug socket	VDMA24364-C1-L	12 V DC	34410	MSFG-12-OD
			24 V DC, 42 V AC	34411	MSFG-24/42-50/60-OD
			42 V DC	34413	MSFG-42-OD
			24 V AC	34415	MSFW-24-50/60-OD
			48 V AC	34418	MSFW-48-50/60-OD
			110 V AC	34420	MSFW-110-50/60-OD
			230 V AC	34422	MSFW-230-50/60-OD
			240 V AC	34424	MSFW-240-50/60-OD
	With plug socket	VDMA24364-C1-L	12 V DC	4526	MSFG-12
			24 V DC, 42 V AC	4527	MSFG-24/42-50/60
			24 V AC	4534	MSFW-24-50/60
			110 V AC	6720	MSFW-110-50/60
			230 V AC	4540	MSFW-230-50/60
Solenoid coil, plug to EN 175301, type A					
	Without plug socket	VDMA24364-C1-L	24 V DC, 42 V AC	34412	MSFG-24/42-50/60-DS-OD
		VDMA24364-B2-L	230 V AC	175118	MSFW-230-50/60-DS-OD
	With plug socket, plug can be repositioned by 180°	VDMA24364-C1-L	24 V DC, 42 V AC	13264	MSFG-24/42-50/60-DS
	Maritime classification ¹⁾ , see certificate		110 V AC	13265	MSFW-110-50/60-DS
			230 V AC	13266	MSFW-230-50/60-DS

1) More information: www.festo.com/catalogue/... → Support/Downloads.