



GE-M

Male Connector
24° Flareless / Metric



R (BSPT) thread

Cutting face DIN 3852, form B, G
(BSPP) thread

TUBE FITTING PART #	END SIZE		d3 (mm)	i (mm)	l1 (mm)	L1 (mm)	S1 (mm)	S2 (mm)	STANDARD Pressure Rating (bar)		
	1	2							EO		
	(mm)	Metric							CF	71	MS
GE04LLM6X1KEG	4	M6 x 1 keg.	—	8	16.0	26	9	10	100		
GE04LLM	4	M8 x 1 keg.	—	8	16.0	26	10	10	100	100	63
GE06LLM	6	M10 x 1 keg.	—	8	14.5	26	11	12	100		63
GE08LLM	8	M10 x 1 keg.	—	8	16.5	28	12	14	100		63
GE06LM	6	M10 x 1	14	8	8.5	23	14	14	315	315	200
GE08LM	8	M12 x 1.5	17	12	10.0	25	17	17	315	315	200
GE10LM	10	M14 x 1.5	19	12	11.0	26	19	19	315	315	200
GE10LM16X1.5	10	M16 x 1.5	21	12	12.0	27	22	19	315	315	
GE10LM18X1.5	10	M18 x 1.5	23	12	12.5	27	24	19	315		
GE10LM22X1.5	10	M22 x 1.5	27	14	14.0	29	27	19	315		
GE12LM14X1.5	12	M14 x 1.5	19	12	11.0	26	19	22	315		
GE12LM	12	M16 x 1.5	21	12	12.5	27	22	22	315	315	
GE12LM18X1.5	12	M18 x 1.5	23	12	12.5	27	24	22	315		
GE12LM22X1.5	12	M22 x 1.5	27	14	14.0	29	27	22	315		
GE15LM16X1.5	15	M16 x 1.5	21	12	13.0	28	24	27	250		
GE15LM	15	M18 x 1.5	23	12	13.5	29	24	27	250		
GE15LM22X1.5	15	M22 x 1.5	27	14	15.0	30	27	27	250		
GE18LM18X1.5	18	M18 x 1.5	23	12	14.0	30	27	32	250		
GE18LM	18	M22 x 1.5	27	14	14.5	31	27	32	250	250	160
GE22LM22X1.5	22	M22 x 1.5	27	14	16.5	33	32	36	160		
GE22LM	22	M26 x 1.5	31	16	16.5	33	32	36	160		100
GE28LM	28	M33 x 2	39	18	17.5	34	41	41	160	160	
GE35LM	35	M42 x 2	49	20	17.5	39	50	50	160		
GE42LM	42	M48 x 2	55	22	19.0	42	55	60	160		
GE06SM	6	M12 x 1.5	17	12	13.0	28	17	17	400		
GE08SM	8	M14 x 1.5	19	12	15.0	30	19	19	400		
GE10SM	10	M16 x 1.5	21	12	15.0	31	22	22	400		
GE12SM	12	M18 x 1.5	23	12	17.0	33	24	24	400		
GE12SM22X1.5	12	M22 x 1.5	27	14	17.5	34	27	24	400		
GE14SM	14	M20 x 1.5	25	14	19.0	37	27	27	400		
GE16SM18X1.5	16	M18 x 1.5	23	12	18.0	36	27	30	400		
GE16SM	16	M22 x 1.5	27	14	18.5	37	27	30	400		
GE20SM	20	M27 x 2	32	16	20.5	42	32	36	400		
GE25SM	25	M33 x 2	39	18	23.0	47	41	46	250		
GE30SM	30	M42 x 2	49	20	23.5	50	50	50	160		
GE38SM	38	M48 x 2	55	22	26.0	57	55	60	160		

Note: "keg." refers to taper threads.

Dimensions and pressures for reference only, subject to change.



Parker Hannifin Corporation
Tube Fittings Division
Columbus, Ohio
<http://www.parker.com/tfd>