

TECHNICAL SPECIFICATION



Stealth™ 9200 Faceshield Goggle N Rated

Stealth™ 9200 Faceshield Goggle N Rated / AGW010-603-000



DESCRIPTION

A unique combination of indirect vented goggle and face protection with a sleek modern design. The Stealth™ 9200 has been engineered to offer outstanding performance, comfort and looks.

OPTIONS

**Stealth™ 9200 Faceshield Goggle N Rated
(AGW010-603-000)**

SAFETY STANDARDS

EN 166 • EN 170



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 24 Oct 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2



Manufacturer's Trademark
JSP Dagger



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



Protection from Liquid Droplets
3



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Resistance to Molten Metals and Hot Solids Helmets (optional)
9



Protection from Large Dust Particles (up to 40 um grain size)
4



Product Weight
202g




Resistance to fogging (optional)
N

FEATURES



Wraparound Lens

Large injection moulded spherical wraparound optically perfect lens for a clear field of vision. With anti-mist, anti-scratch and class 1 optics.



Comfort

Ultra soft housing and dual injection frame provides a soft comfortable fit that moulds to fit almost any face shape.



Adjustable

Wide elastic headband with easy quick release clipping buckle makes it comfortable and suitable for most head sizes.



Moveable Faceshield

Lighter than a standard faceshield, this polycarbonate model can be easily lifted out of the way when not in use.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Agricultural

Airports

Construction and Infrastructure

Facilities Management

Food and Drink Manufacturing

Manufacturing

Mining, Aggregates and Quarrying

Rail and Tunnelling

Renewable, Wind and Solar Energy

Scaffolding and Roofing

Sole Trader

Utilities Contractors

RANGE

DOWNLOADS

**STEALTH
9200**



[Image Pack \(ZIP\)](#)



[doc-stealth-9200.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 24 Oct 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

