

80

## **Contractors' Tools**

## **Insulated Range**

The orange outer sheath (also referred to as the abrasive guard) has excellent high voltage protection, is environment sealed and resistant to impact and abrasion

2026PF/INS12 - Trenching Shovel 2027PF/INS12 - Cable Laying 2861PF/INS12 - Grafting Spade • Handle Type: YD Insulated • Handle Type: YD Insulated · Handle Type: YD Insulated Blade Size: • Blade Size: Blade Size: 276mm (11") x 172mm (7") 276mm (11") x 119mm (43/4") 320mm (125/8") x 160mm (61/4") • Handle Length: 733mm • Handle Length: 733mm • Handle Length: 733mm (287/8") (287/8") (287/8")2036PF/INS12 -1180PF/INS12 -2159PF/INS12 -**Digging Spade General Service Newcastle Drainer**  Handle Type: YD Insulated • Handle Type: YD Insulated • Handle Type: YD Insulated Blade Size: Blade Size: Head Size: 405mm (161/4") x 105mm (4") 289mm (113/8") x 190mm (71/2") 240mm (9½") x 195mm (7¾") • Handle Length: 733mm (287/8") Handle Length: 733mm (287/8" • Handle Length: 733mm (287/8")

The product is considered to comply with the British Standard only if no electric breakdown occurred during testing and the leakage current did not exceed 1mA specified

## CBCP114/INS -CBCB114/INS -DSH/INS -**Crowbar Chisel & Point Crowbar Chisel & Blunt Double Shovel Holer** • Handle Type: Insulated · Handle Type: Insulated · Handle Type: Insulated • Blade Width: 43mm (15/8") • Blade Width: 43mm (15/8") • Handles: 32mm (11/4") Dia • Overall Length: 1840mm (72") • Overall Length: 1840mm (72") • Blade Length: 355mm (14") • Max Open Width: 370mm (141/2") Overall Length: 1710mm (671/4" • Weight: 7.7kgs





## Prong Fork\* Handle Type: YD Insulated Head Size: 195mm (7¾") x 76mm (3") Handle Length: 730mm (28¾") Ideal for use in confined spaces, minimises potential cable damage

\*Load test not applicable

www.spear-and-jackson.com 81