



Harmony, Socket, for RUMC2 relays, 10 A, screw connectors, mixed contact

RUZC2M

١	V	1	а	ı	r	

Range of product	Harmony Electromechanical Relays Harmony Timer Relays
Product or component type	Socket
Contact terminal arrangement	Mixed
Product compatibility	Plug-in relay RUM with 2 C/O contact Plug-in relay RE48 with 2 C/O contact Plug-in relay RE48 with 1 C/O + 1 C/O contact
Shape of pin	Cylindrical
Device short name	RUZ
Sale per indivisible quantity	10

Complementary

[Ith] conventional free air thermal current [Ue] rated operational voltage < 250 V Tightening torque < 1 N.m for M3.5 screw(s) Fixing mode By screw (panel) Clip-on (35 mm symmetrical DIN rail) Marking CE Width 38 mm Net weight 0.054 kg	· · · · · · · · · · · · · · · · ·	
Tightening torque < 1 N.m for M3.5 screw(s) Fixing mode By screw (panel) Clip-on (35 mm symmetrical DIN rail) Marking CE Width 38 mm		10 A
Fixing mode By screw (panel) Clip-on (35 mm symmetrical DIN rail) Marking CE Width 38 mm	[Ue] rated operational voltage	< 250 V
Clip-on (35 mm symmetrical DIN rail) Marking CE Width 38 mm	Tightening torque	< 1 N.m for M3.5 screw(s)
Width 38 mm	Fixing mode	
	Marking	CE
Net weight 0.054 kg	Width	38 mm
	Net weight	0.054 kg

Environment

Connections - terminals	Connector, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm² (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end
Standards	IEC 61984
Product certifications	UL CSA
Ambient air temperature for storage	-4085 °C
Ambient air temperature for operation	-4055 °C
IP degree of protection	IP20 conforming to EN/IEC 60529

Dielectric strength	2500 V
Dooking Units	
Packing Units	DOE
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.005 kg
Package 1 Height	8.4 mm
Package 1 width	8.6 mm
Package 1 Length	14.6 mm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	629 g
Package 2 Height	8.4 cm
Package 2 width	8.6 cm
Package 2 Length	14.6 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	200
Package 3 Weight	12.58 kg
Package 3 Height	28.5 cm
Package 3 width	29.9 cm
Package 3 Length	39.8 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
ELL Boll C Directive	Dro active compliance (Product out of ELLPSUS less)
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty			
Warranty	18 months		

Product data sheet

RUZC2M

Dimensions Drawings

Socket

8-Pin Socket



