

The Timken Company 4500 Mt Pleasant St. NW N. Canton, OH 44720


Phone: (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number 66462, Tapered Roller Bearings - Single Cups - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





<u>Specifications</u> | <u>Dimensions</u> | <u>Abutment and Fillet Dimensions</u> | <u>Factors</u>

Specifications			
	Series	66000	
	Cup Part Number	66462	
	Design Units	Imperial	

Dimensions -						
	D - Cup Outer Diameter	4.6250 in 117.475 mm				
	C - Cup Width	0.9375 in 23.813 mm				

Abutment and Fillet Dimensions	-

r - Cup Backface "To Clear"	0.130 in
Radius ¹	3.3 mm
Da - Cup Frontface Backing	4.41 in
Diameter	112.00 mm
Db - Cup Backface Backing	3.94 in
Diameter	100.08 mm


Factors -				
	e - ISO Factor ²	0.63		
	Y - ISO Factor ³	0.96		
	Cg - Geometry Factor ⁴	0.0751		

¹ These maximum fillet radii will be cleared by the bearing corners.

 $^{^2}$ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

 $^{^3}$ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁴ Geometry constant for Lubrication Life Adjustment Factor a3l.



IMPERIAL UNITS

66462 SINGLE TAPERED CUP

THE TIMKEN COMPANY NORTH CANTON, OHIO USA

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY