


Air solenoid valve VUVG

Part number: 564212

FESTO



Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Valve function	2x3/2, open/closed, monostable 5/3, closed 5/2, monostable 2x3/2, closed, monostable 5/3, pressurized 5/2, bistable 5/3, exhausted 2x3/2, open, monostable
Lap	Overlap Indefinite overlap
Operating pressure	-0.09 MPa ... 1 MPa
Actuation type	Electrical
Valve size	10 mm 18 mm 14 mm
Standard nominal flow rate	90 l/min ... 1380 l/min
Pneumatic working port	QS-6 QS-8 QS-3 QS-5/32 G1/8 M7 G1/4 QS-1/8 QS-3/8 M3 QS-4 QS-5/16 QS-1/4 QS-3/16 M5 QS-10 Flange
Operating voltage	12V DC 24V DC 5V DC
Operating pressure	-0.9 bar ... 10 bar
Design	Piston gate valve
Reset method	Mechanical spring Pneumatic spring
Degree of protection	IP40 IP65 With plug socket

Feature	Value
Certification	RCM compliance mark c CSA us (OL) c UL us - Recognized (OL)
Type code	VUVG
Exhaust air function	With flow control option
Sealing principle	Soft
Mounting position	Any
Manual override	Detenting Non-detenting Covered
Type of control	Pilot-controlled
Pilot air supply port	External Internal
Duty cycle	100%
Permissible voltage fluctuations	+/- 10 %
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive As per EU RoHS directive
Restricted ambient and media temperature	-5 - 50 °C Without holding power reduction
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Temperature of medium	-5 °C ... 60 °C
Ambient temperature	-5 °C ... 60 °C
Electrical connection	Via electrical sub-base
Type of mounting	On terminal strip With through-hole Optionally:
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Seals material	HNBR NBR
Housing material	Wrought aluminum alloy