





REGULAR LOAD

CASSIDA GREASE RLS 000 | 00 | 0 | 1 | 2




	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code
CASSIDA GREASE RLS 000	AICx	100	13	-50 to +100 (upper peak: +120)	<000	
CASSIDA GREASE RLS 00	AICx	100	13	-45 to +100 (upper peak: +120)	00	
CASSIDA GREASE RLS 0	AICx	150	18	-40 to +100 (upper peak: +120)	0	
CASSIDA GREASE RLS 1	AICx	150	18	-40 to +120 (upper peak: +140)	1	
CASSIDA GREASE RLS 2	AICx	150	18	-35 to +120 (upper peak: +140)	2	

High-performance, regular-load aluminium complex greases with synthetic base fluid.

Main application: For use on bearings, bushings and linkages on food manufacturing equipment. CASSIDA GREASE RLS 0 and 00 are particularly recommended for centralised lube systems or other similar systems where an NLGI 2 grease may be difficult to dispense.

EXTREME PRESSURE

CASSIDA GREASE EPS 00 | 1 | 2



	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code
CASSIDA GREASE EPS 00	AICx	220	25	-45 to +100 (upper peak: +120)	00	
CASSIDA GREASE EPS 1	AICx	220	25	-40 to +120 (upper peak: +140)	1	
CASSIDA GREASE EPS 2	AICx	220	25	-35 to +120 (upper peak: +140)	2	

High-performance, extreme-pressure aluminium complex greases with synthetic base fluid.

Main application: For use on bearings, bushings and linkages on food manufacturing equipment, particularly where high pressure and loads, high temperatures and water spray occur. CASSIDA GREASE EPS 00 is especially recommended for centralised lube systems and enclosed gears.

HEAVY DUTY

CASSIDA GREASE HDS 00 | 2

	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code
CASSIDA GREASE HDS 00	AICX	800	68	-35 to +120 (upper peak: +120)	00	
CASSIDA GREASE HDS 2	AICX	800	68	-35 to +120 (upper peak: +140)	2	

High-performance, high-viscosity heavy-duty aluminium complex greases with synthetic base fluid.

Main application: For use on bearings, bushings and linkages on food manufacturing equipment, particularly where slower speeds, high pressure and loads, high temperatures and water spray are present. CASSIDA GREASE HDS 00 is recommended for open gears and centralised lube systems.