


Technical datasheet

4T-749A

Single row tapered roller bearings

Mounted cone, sheet metal cage

Visual(s)



Product definition

d	82.55 mm
B	46.67 mm
d1	114.5 mm
e	0.33
Y2	1.84
Y0	1.01
Brand	NTN

Product performance

Dynamic load, C	261 kN
Rating life coefficient, A2	1.4
Static load, C0	360 kN
Fatigue limit load, Cu	42 kN
Nlim (oil)	3,200 rpm
Nlim (grease)	2,400 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.55 Hz
Characteristic outer ring frequency, BPF0	7.69 Hz
Characteristic inner ring frequency, BPFI	10.31 Hz

Abutment dimensions

ra max	3.5 mm
--------	--------

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table