

Stainless Steel Compression Fittings

1866 3-Piece Reducer

Stainless steel 316L		ØD1	ØD2		F	kg
		6	8	1866 06 08	14	0.011
			10	1866 06 10	19	0.028
			12	1866 06 12	22	0.040
		8	10	1866 08 10	19	0.026
			12	1866 08 12	22	0.037
			16	1866 08 16	27	0.071
		10	12	1866 10 12	22	0.034
			16	1866 10 16	27	0.065
			12	1866 12 16	27	0.061

1824 Stainless Steel Olive

Stainless steel 316L	ØD		kg
	6	1824 06 00	0.001
	8	1824 08 00	0.001
	10	1824 10 00	0.003
	12	1824 12 00	0.004
	16	1824 16 00	0.005

1810 Stainless Steel Nut

Stainless steel 316L	ØD	C		F	L	kg
	6	M10x1	1810 06 00	13	11	0.007
	8	M12x1	1810 08 00	14	13	0.008
	10	M16x1.5	1810 10 00	19	15	0.017
	12	M18x1.5	1810 12 00	22	15	0.024
	16	M22x1.5	1810 16 00	27	17	0.041

1822 Barb Adaptor for Hose

Stainless steel 316L	ØD1	ØD2		ØD3	L	L1	ØT min	kg
	6	7	1822 06 07	9	37.5	22.5	6	0.006
		6	1822 08 06	8	40	22.5	5	0.007
		7	1822 08 07	9	40	22.5	6	0.007
	8	10	1822 08 10	12.5	40	22.5	9	0.011
		7	1822 10 07	9	43	22.5	6	0.009
		10	1822 10 10	12.5	43	22.5	9	0.013
	10	10	1822 12 10	12.2	43	22.5	9	0.012
		13	1822 12 13	15	50	29.5	13	0.016

1827 Stainless Steel Tube Support

Stainless steel 316L	ØD1	ØD2		L	kg
	6	4	1827 06 00	11.5	0.001
	8	6	1827 08 00	14	0.001
	10	8	1827 10 00	18	0.001
	12	9	1827 12 09	18	0.001
	12	10	1827 12 00	18	0.001
	16	14	1827 16 00	18	0.002

This tube support is necessary when using fluoropolymer tubing at all temperatures compatible with the fitting/tubing assembly.