

TECHNICAL DATASHEET

Updated: 28/11/23

ADHESIVE DUCT TAPE

| Article # | EAN | Product |
|-----------|---------------|------------------|
| 886635 | 3660338400438 | Duct tape, GREY |
| 886636 | 3660338400445 | Duct tape, BLACK |

Description

Premium quality, higher adhesion version, polyethylene laminated waterproof cloth tape. It is coated with a pressure sensitive, natural rubber resin adhesive. Good water resistance. Excellent adhesion and ultimate bond strength. Flexible and conformable. Service temperature:

-15°C to +75°C. Good all-purpose product. Easy unwind. Easy tear by hand.
Good initial tack. Good low temperature performance for winter applications. REACH and RoHS compliant.

Applications

Designed as a general purpose waterproof cloth tape for applications requiring additional strength and adhesion. Used for sealing, bundling, short term masking and protecting. Excellent for jointing polyethylene sheeting in asbestos removal applications. Suitable for double glazing unit sealing. Medium temperature duct sealing. Carpet joining and edging.

Characteristics

| Colour | Width | Length | Thickness |
|--------|-------|--------|-----------|
| | (mm) | (M) | (mm) |
| GREY | 50.0 | 50.0 | 0.18 |
| BLACK | 50.0 | 50.0 | 0.18 |

Instructions & storage

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

Packaging

- Unit