

Gloves G-HIGH CUT PU F

Update: 02/10/2023

Item #	EAN	Size
895948	3660338482649	6
895949	3660338482656	7
895950	3660338482663	8
895951	3660338482670	9
895952	3660338482687	10
895953	3660338482694	11



Description

Seamless knitted gloves in 15 gauge HPPE fibre.
For use on touch screens, thumb-index reinforcement.
Water-based polyurethane coating on palm and fingertips.
High cut protection, excellent in dry environments.
Aeronautics, assembly of metal parts, finishing work, glassmaking, maintenance.

Characteristics

- Materials: HPPE FIBRE
- Coating: Water-based polyurethane on palm and fingertips.
- Gauge: 15

Certification

- Complies with Regulation (EU) 2016/425 on Personal Protective Equipment (PPE)
- Category II
- EN 420 : 2003 + A1: 2009. Protective gloves - General requirements and test methods
- EN 388: 2016. Protective gloves - Protection against mechanical risks



EN388 :2016	Level 1	Level 2	Level 3	Level 4	Level 5	Levels G-HIGH CUT PU F
Abrasion resistance (number of cycles)	100	500	2000	8000	-	4
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	X
Tear resistance (in newtons)	10	25	50	75	-	4
Puncture resistance (in newtons)	20	60	100	150	-	3

Shear strength (N) (according to EN ISO 13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Levels G-HIGH CUT PU F
	2	5	10	15	22	30	F

Packaging

- Packs of 12 pairs
- box of 120 pairs