



Technical datasheet

NU2212EG1C3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Visual(s)



Product definition

d	60 mm
D	110 mm
B	28 mm
E	100 mm
F	72 mm
rs min	1.5 mm
r1s min	1.5 mm
Radial clearance class	C3
Mass (without HJ ring)	1.12 kg
Brand	NTN

Product performance

Dynamic load, C	131 kN
Static load, C0	157 kN
Fatigue limit load, Cu	19.1 kN
Nlim (oil)	6,100 rpm
Nlim (grease)	5,200 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.98 Hz
Characteristic outer ring frequency, BPF0	6.7 Hz
Characteristic inner ring frequency, BPF1	9.3 Hz

Abutment dimensions

da min	68 mm
da max	71 mm
db min	75 mm
Da max	102 mm
ra max	1.5 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$