



## Housing units GRA40-XL (Series GRA)

three/four-bolt flanged housing units, sheet steel, eccentric locking collar,  
P seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	40 mm
H	147,5 mm
B <sub>1</sub>	43,8 mm
A	10,3 mm
d <sub>3 max</sub>	58 mm
J	119 mm
N	13,5 mm
n	4      Number of screw holes
S	3,5 mm
U	36,2 mm
V	90 mm

m	1,36 kg	Mass
C <sub>0r G</sub>	7700 N	Load carrying capacity of housing, radial
C <sub>r</sub>	34500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	19800 N	Basic static load rating, radial
	FLAN80-MSB (1 X) / FLAN80-MSA (1 X)	Designation of housing
	GRAE40-XL-NPP-B	Designation of bearing



