



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 34301, Tapered Roller Bearings - Single Cones - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	34000
Cone Part Number	34301
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions)¹	40000 lbf 178000 N
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions)²	10400 lbf 46100 N



Dimensions

d - Cone Bore	3 in 76.2 mm
B - Cone Width	0.9060 in 23.012 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius³	0.140 in 3.6 mm
da - Cone Frontface Backing Diameter	3.27 in 83 mm
db - Cone Backface Backing Diameter	3.5 in 89 mm
Ab - Cage-Cone Frontface Clearance	0.1 in 2.5 mm
Aa - Cage-Cone Backface Clearance	0.09 in 2.3 mm
a - Effective Center Location⁴	0.06 in 1.5 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁵	5960 lbf 26500 N
C1 - Dynamic Radial Rating (1 million revolutions)⁶	23000 lbf 102000 N
C0 - Static Radial Rating	30600 lbf 136000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁷	4600 lbf 20500 N

Factors

K - Factor⁸	1.3
G1 - Heat Generation Factor (Roller-Raceway)	69.3
G2 - Heat Generation Factor (Rib-Roller End)	27
Cg - Geometry Factor⁹	0.109

¹ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

² Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

³ These maximum fillet radii will be cleared by the bearing corners.

⁴ Negative value indicates effective center inside cone backface.


⁵ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁶ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁷ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ Geometry constant for Lubrication Life Adjustment Factor a_3 .



IMPERIAL UNITS

Number of Rollers Per Row24	TIMKEN®		34301 Tapered Roller Bearings - Single Cones - Imperial	
	THE TIMKEN COMPANY NORTH CANTON, OHIO USA		K Factor1.3 Dynamic Radial Rating - C905960 lbf Dynamic Thrust Rating - Ca904600 lbf Dynamic Radial Rating - C123000 lbf	