



## COBAmat® Light

Standing the test of time, our original safety matting



- The original premium multi-purpose safety mat widely used across industry today.
- An ideal choice for longer production lines, or for covering mezzanine floors.
- Available in four vibrant colours and four weave (hole) sizes to suit the application.
- Vinyl strips are interwoven, rather than welded, for better flexibility and lower risk of breaking.
- Cross-ribbed grip to reduce slipping.
- Fully reversible for added longevity.
- Suitable for use in wet and dry environments, or where swarf and debris cause problems.
- Fire tested to BS EN 13501-1 and slip tested to DIN 51130.
- Widely used in a range of industrial and non-industrial environments, both wet and dry.
- 22 mm x 22 mm hole size.

### Parts

Part Number	Size	Colour	Weight
CO010605	0.6 m x 5 m	Black	
CO020605	0.6 m x 5 m	Blue	
CO030605	0.6 m x 5 m	Red	
CO040605	0.6 m x 5 m	Green	
CO010610	0.6 m x 10 m	Black	
CO020610	0.6 m x 10 m	Blue	
CO030610	0.6 m x 10 m	Red	
CO040610	0.6 m x 10 m	Green	
CO010905	0.9 m x 5 m	Black	
CO020905	0.9 m x 5 m	Blue	
CO030905	0.9 m x 5 m	Red	
CO040905	0.9 m x 5 m	Green	
CO010910	0.9 m x 10 m	Black	
CO020910	0.9 m x 10 m	Blue	
CO030910	0.9 m x 10 m	Red	
CO040910	0.9 m x 10 m	Green	
CO011205	1.2 m x 5 m	Black	
CO021205	1.2 m x 5 m	Blue	

### Technical Specification

<b>Material</b>	PVC
<b>Surface Finish</b>	Cross ribbed lattice
<b>Product Height</b>	12 mm
<b>Hole Size</b>	30 mm x 30 mm
<b>Operating Temperature</b>	-20°C to +60°C
<b>Resistance to Chemicals</b>	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details
<b>Environmental Resistance</b>	Suitable for wet and dry environments, indoors or outdoors
<b>UV Resistance</b>	Resistant to UV, but please note that red is not colourfast in direct sunlight
<b>Typical Applications</b>	General industrial, Engineering, Machine tool areas where swarf prevalent
<b>Installation Method</b>	Loose lay, reversible
<b>Accessories</b>	Factory fitted edging where required

## Technical Specification

<b>Cleaning Method</b>	Pressure hose with mild detergent if required
------------------------	---

<b>Country of Origin</b>	UK
--------------------------	----

<b>Slip Tested to</b>	DIN 51130 - R10
-----------------------	-----------------

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email [sales@cobaeurope.com](mailto:sales@cobaeurope.com)