The future of wet and dry vacuum cleaning

The VL500 series of wet and dry vacuum cleaners is offering performance and reliability that ensure low total cost of ownership and at the same time has features making daily cleaning tasks easier, faster and safer. VL500 is ideally suited for hotels, contract cleaners, education, exhibition and conference centers as well as public buildings, manufacturing and industrial applications. A failsafe filter design makes operation easy due to the ability to have individual wet and dry filters working simultaneously. Each filter is specific for either a wet or dry application ensuring maximum performance. With the special dual filtration system, Nilfisk VL500 can be used in whatever environment, wet or dry, without the need to change filters. The unique design and features of VL500 is developed in partnership with Nilfisk customers. The VL500 is available in different configurations and various container sizes; 35, 55 and 75 liter. Go to the specific factsheet for further information

- Empty the container without having to remove the motor head makes operation fast and easy without risk of damage to critical components
- By transferring the weight as you lift the container, the Nilfisk Ergo
 Tipping system enables you to empty a completely filled container of
 fluid without excessive effort



Picture shown may not represent model quoted

- · Easy changing of filters with the hinged motor head protects the machines and speeds up the process
- · With the dual filtration system, the VL500 can be used in both wet or dry applications without the need to change filters

Standard equipment

	Included accessories	Ref. no.	Min. required	VL500 55-1 BSF 220-240V/50-60 EU	VL500 55-2 BSF 220-240V/50-60 EU	VL500 55-1 EDF 220-240V/50-60 EU
Hose Vacuum	n Cleaner					
9	HOSE D40 2.5M CPL	107407336	1	•	•	•
Vac Nozzle W	/et					
1	FLOOR NOZZLE D40 RUBBER STRIP	107407338	1			
	HARDFLOOR NOZZLE 400MM X Ø40MM - KIT	107416577	1	•	•	•
Hard Floor No	ozzle					
	FLOOR NOZZLE D40 BRUSH	107407339	1	•	•	•
Crevice Nozz	Crevice Nozzle					
	CREVICE NOZZLE D40	107408850	1	•	•	•
Filter						
	CARTRIDGE FILTER	107407300	1			•
	SACK FILTER	107407304	1	•	•	
Special Filter	Special Filter					



The future of wet and dry vacuum cleaning			
Model	VL500 55-1 BSF 220-240V/50-60 EU	VL500 55-2 BSF 220-240V/50-60 EU	VL500 55-1 EDF 220-240V/50-60 EU
Ref. no.	107405156	107405157	107405161
PRODUCT FEATURES			
Dual power		•	
Tube holder	•	•	•
Dual filter system			•
Folding transport handle			•
Adjustable handle			•
Storage of accessories	•	•	•
Drain hose	•	•	•
Ergo tipping			•
Model	VL500 55-2 EDF 220-240V/50-60 EU	VL500 55-2 EDF 220-240V/50 UK	VL500 55-2 EDF 230V/50 CH
Ref. no.	107405162	107405173	107405206
PRODUCT FEATURES			
Dual power	•	•	•
Tube holder	•	•	•
Dual filter system	•	•	•
Folding transport handle	•	•	•
Adjustable handle	•	•	•
Storage of accessories	•	•	•
Drain hose	•	•	•
Ergo tipping	•	•	•
Model		VL500 55-1 BDF 220-240V/50-60 EU	VL500 55-2 BDF 220-240V/50-60 EU
Ref. no.		107407459	107407460
PRODUCT FEATURES			
Dual power			•
Tube holder		•	•
Dual filter system		•	•
Folding transport handle			
Adjustable handle			
Storage of accessories		•	•
Drain hose		•	•
Ergo tipping			



T. C.				
The future	OT WAT	and di	พาเมาระง งา	cleaning
THE luture	OI WEL	and di	y vacuum	Cicaring

Technical specifications	VL500 55-1 BSF 220-240V/50-60 EU	VL500 55-2 BSF 220-240V/50-60 EU	VL500 55-1 EDF 220-240V/50-60 EU
Cable length (m)/ plug type	10/EU	10/EU	10/EU
Voltage/frequency (V/Hz)	220-240/50-60	220-240/50-60	220-240/50-60
IP protection class	IP24	IP24	IP24
Rated power (W)	1350	2500	1350
Power Piec (W)	1250	2400	1250
Suction power end of tube (W)	200	200	200
Airflow (I/sec.)	48	72	48
Vacuum at nozzle (kPa)	20	21	20
Sound pressure level (dB(A) BS 5415)	64	66	64
Sound power level (dB(A) IEC 704)	82	84	82
Tank capacity (I)	55	55	55
Dust bag capacity (I)	28	28	28
Sack filter area (cm²)	1840	1840	-
Wet filter area (cm²)	-	-	1840
Cartridge filter area (cm²)	-	-	4410
Hose length (m)	2.5	2.5	2.5
Inlet (mm)	40	40	40
Length x width x height (mm)	840x620x1000	840x620x1000	660x620x890
Weight (kg)	23.5	24.5	26.5
Technical specifications	VL500 55-2 EDF 220-240V/50-60 EU	VL500 55-2 EDF 220-240V/50 UK	VL500 55-2 EDF 230V/50 CH
Cable length (m)/ plug type	10/EU	10/UK	10/CH
Voltage/frequency (V/Hz)	220-240/50-60	220-240/50-60	220-240/50-60
IP protection class	IP24	IP24	IP24
Rated power (W)	2500	2500	2500
Power Piec (W)	2400	2400	2400
Suction power end of tube (W)	200	200	200
Airflow (I/sec.)	72	72	72
Vacuum at nozzle (kPa)	21	21	21
Sound pressure level (dB(A) BS 5415)	66	66	66
Sound power level (dB(A) IEC 704)	84	84	84
Tank capacity (I)	55	55	55
Dust bag capacity (I)	28	28	28
Sack filter area (cm²)	-	-	-
11.4 (1).			
Wet filter area (cm²)	1840	1840	1840
Wet filter area (cm²) Cartridge filter area (cm²)	1840 4410	1840 4410	1840 4410



The future of wet and dry vacuum cleaning

Technical specifications	VL500 55-2 EDF 220-240V/50-60 EU	VL500 55-2 EDF 220-240V/50 UK	VL500 55-2 EDF 230V/50 CH
Inlet (mm)	40	40	40
Length x width x height (mm)	660x620x890	660x620x890	660x620x890
Weight (kg)	27.5	27.5	27.5
Technical specifications		VL500 55-1 BDF 220-240V/50-60 EU	VL500 55-2 BDF 220-240V/50-60 EU
Cable length (m)/ plug type		10/EU	10/EU
Voltage/frequency (V/Hz)		220-240/50-60	220-240/50-60
IP protection class		IP24	IP24
Rated power (W)		1350	2500
Power Piec (W)		1250	2400
Suction power end of tube (W)		200	200
Airflow (I/sec.)		48	72
Vacuum at nozzle (kPa)		20	21
Sound pressure level (dB(A) BS 5415)		64	66
Sound power level (dB(A) IEC 704)		82	84
Tank capacity (I)		55	55
Dust bag capacity (I)		28	28
Sack filter area (cm²)		-	-
Wet filter area (cm²)		1840	1840
Cartridge filter area (cm²)		4410	4410
Hose length (m)		2.5	2.5
Inlet (mm)		40	40
Length x width x height (mm)		840x620x1000	840x620x1000
Weight (kg)		24.5	25.5

[●] Standard equipment, ○ Supplementary accessories, □ Mountable equipment

	Accessories	Ref. no.	Min. required	VL500 55-1 BSF 220-240V/50-60 EU	VL500 55-2 BSF 220-240V/50-60 EU	VL500 55-1 EDF 220-240V/50-60 EU
System 50 Ho	System 50 Hose Vacuum Cleaner					
	HOSE CONNECTION Ø50 PVC	6330	0	0	0	0
	HOSE UNIVERSAL Ø50 EVA PER METER	11984	0	0	0	0
	SLEEVE CPL - VACUUM SIDE - D50/D50	15101	0	0	0	0
Squeegee, Bl	Squeegee, Blade, Skirt and Splash Guard					
	SQUEEGEE COMPLETE ANTHRACIT	107407051	1	0	0	0
Filter Bag	Filter Bag					

