



DELIVERY
10-15 DAYS



1 YEAR
WARRANTY



MAX LOAD
150 KG



REGULAR
USAGE

Mobile Safety Steps

Strong tubular steel construction for commercial applications with double handrail, toe-boarded platform and enclosed guardrail for assured working and stock picking.

- Locking device and anti-ascent bar
- Comfortable 560 x 400mm platform for assured stock picking
- Fully welded tubular steel construction
- Choice of anti-slip or punched 560 x 180mm deep treads
- Easy one-user manoeuvrability
- EN131-7



KM 608967
BS EN 131-7

MOBILE SAFETY STEPS									
SKU		Tread Count*	Approx. Working Height†	Platform Height	Overall Height	Width (m)	Depth (m)	Punched Weight (kg)	Anti-slip Weight (kg)
Punched	Anti-Slip		(m)	(m)	(m)				
2017-003	2018-003	3	2.35	0.75	1.75	0.86	0.81	28.0	28.0
2017-004	2018-004	4	2.60	1.00	2.00	0.91	0.97	32.0	32.0
2017-005	2018-005	5	2.85	1.25	2.25	0.95	1.12	55.0	55.0
2017-006	2018-006	6	3.10	1.50	2.50	1.00	1.28	62.0	62.0
2017-007	2018-007	7	3.35	1.75	2.75	1.04	1.43	70.0	70.0
2017-008	2018-008	8	3.60	2.00	3.00	1.09	1.59	78.0	78.0
2017-009	2018-009	9	3.85	2.25	3.25	1.13	1.74	90.0	90.0
2017-010	2018-010	10	4.10	2.50	3.50	1.18	1.90	98.0	98.0
2017-011	2018-011	11	4.35	2.75	3.75	1.22	2.05	106.0	106.0
2017-012	2018-012	12	4.60	3.00	4.00	1.27	2.21	116.0	116.0
2017-013	2018-013	13	4.85	3.25	4.25	1.31	2.36	122.0	122.0
2017-014	2018-014	14	5.10	3.50	4.50	1.36	2.52	130.0	130.0
2017-015	2018-015	15	5.35	3.75	4.75	1.40	2.67	138.0	138.0

*Tread count includes top platform step

†3 Tread steps are not fitted with the anti-descent or locking bar

Note that this unit is supplied in 2 x packages over 10 steps and above

