

Series NVZ100

How To Order: Series NVZ100

Voltage •	
* 1	100V AC 50/60Hz
* 2	200V AC 50/60Hz
3	115VAC60Hz (110VAC%Hz)
4	230VAC60Hz (220VAC%Hz)
5	24V DC
6	12V DC
* 9	Others

*Consult factory for availability.

Indicator light and surge voltage suppressor	
	Without indicator light and surge voltage suppressor
Z†	With indicator light and surge voltage suppressor
S*	With surge voltage suppressor

Z option not available for grommet type.
*Grommet type only.

Surge voltage suppressor of grommet type.



Body Ported


NVZ1 1 0-5 L Z-M5-

Type of actuation •

1	Normally closed
2	Normally open

Optional accessory

F:Foot bracket
DXT170-34-1A









(factory assembled)

Port Size

M5 10-32Nom.(M5 × 0.8)

Electrical entry

G:Grommet  Lead wire length :12inch (300mm)		*H:Grommet  Lead wire length :24inch (600mm)		MO:M type plug connector without connector 	
L:L type plug connector with lead wire  Lead wire length :12inch (300mm)		M:M type plug connector with lead wire  Lead wire length :12inch (300mm)		LO:L type plug connector without connector 	

*Special Order Only.

How To Order/ Connector Ass'y

DXT170-80-A-

Lead wire color •

* 1	Blue/Blue
* 2	Red/Red
3	Gray/Gray
4	Red/Black(DC)

*Special Order Only.

Lead wire length

	12 inch (300mm) Std.
6	24inch (600mm)
10	40inch (1000mm)
15	60inch (1500mm)
20	80inch (2000mm)
25	100inch (2500mm)
30	120inch (3000mm)

When ordering the valve and long connector ass'y include both the valve and connector ass'y product numbers.

Example: In case of 80 inch lead wire length
NVZ110-5LO-M5
DXT170-80-4A-20