

TECHNICAL DATASHEET

Updated: 28/11/23

PVC DOUBLE-SIDED TAPE

Article #	EAN	Product	
886649	3660338400544	PVC DST, 19mm	
886650	3660338400551	PVC DST, 25mm	
886651	3660338400568	PVC DST, 50mm	



Description

High performance double-sided tape based on a PVC film. The tape is coated on both sided with an aggressive, acrylic based adhesive (Medium Soft 1), protected by a 120 gsm, white coloured, polycoated paper release liner. Recommended for bonding, splicing, laminating and product assembly applications. Service temperature: -30°C to +70°C. Suitable for rough surfaces. Solvent resistant.

Applications

Bonds Mirrors. Trim attachment. Point of sale assembly. Bonds rubber profiles and weather strips. Bonds a wide variety of similar and dissimilar substrates..

Characteristics

Colour	Width (mm)	Length (M)	Thickness (mm)
TRANSPARENT	19.0	50.0	0.24
TRANSPARENT	25.0	50.0	0.24
TRANSPARENT	50.0	50.0	0.24

Instructions & storage

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

Packaging

- Unit