



COBAmat® Inter

Standing the test of time, our original safety matting



- The original premium multi-purpose safety mat widely used across industry today.
- An ideal choice for longer production lines, or for covering mezzanine floors.
- Available in four vibrant colours and four weave (hole) sizes to suit the application.
- Vinyl strips are interwoven, rather than welded, for better flexibility and lower risk of breaking.
- Cross-ribbed grip to reduce slipping.
- Fully reversible for added longevity.
- Suitable for use in wet and dry environments, or where swarf and debris cause problems.
- Fire tested to BS EN 13501-1 and slip tested to DIN 51130.
- Widely used in a range of industrial and non-industrial environments, both wet and dry.
- 30 mm x 10 mm hole size.

Parts

Part Number	Size	Colour	Weight
CE010605	0.6 m x 5 m	Black	
CE020605	0.6 m x 5 m	Blue	
CE030605	0.6 m x 5 m	Red	
CE040605	0.6 m x 5 m	Green	
CE010610	0.6 m x 10 m	Black	
CE020610	0.6 m x 10 m	Blue	
CE030610	0.6 m x 10 m	Red	
CE040610	0.6 m x 10 m	Green	
CE010905	0.9 m x 5 m	Black	
CE020905	0.9 m x 5 m	Blue	
CE030905	0.9 m x 5 m	Red	
CE040905	0.9 m x 5 m	Green	
CE010910	0.9 m x 10 m	Black	
CE020910	0.9 m x 10 m	Blue	
CE030910	0.9 m x 10 m	Red	
CE040910	0.9 m x 10 m	Green	
CE011205	1.2 m x 5 m	Black	
CE021205	1.2 m x 5 m	Blue	

Technical Specification

Material	PVC
Surface Finish	Cross ribbed lattice
Product Height	12 mm
Hole Size	30 mm x 10 mm
Operating Temperature	-20°C to +60°C
Resistance to Chemicals	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details
Environmental Resistance	Suitable for wet and dry environments, indoors or outdoors
UV Resistance	Resistant to UV, but please note that red is not colourfast in direct sunlight
Typical Applications	General industrial, Engineering, Machine tool areas
Installation Method	Loose lay, reversible
Accessories	Factory fitted edging where required

Technical Specification

Cleaning Method	Pressure hose with mild detergent if required
Country of Origin	UK
Slip Tested to	DIN 51130 - R10

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email sales@cobaeurope.com