



Technical data

4T-HM813840/HM813810

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Visual(s)



Product definition

d	55.56 mm
D	127 mm
B	36.51 mm
C	26.99 mm
T	36.51 mm
d1	100 mm
a	32.81 mm
e	0.5
Y2	1.2
Y0	0.66
Mass	2.34 kg
Brand	NTN

Product performance

Dynamic load, C	163 kN
Rating life coefficient, A2	1.4
Static load, C0	228 kN
Fatigue limit load, Cu	27.8 kN
Nlim (oil)	3,800 Tr/min
Nlim (grease)	2,900 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.34 Hz
Characteristic outer ring frequency, BPF0	8.73 Hz
Characteristic inner ring frequency, BPFI	11.27 Hz

Abutment dimensions

ra max	3.5 mm
r1a max	3.3 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table