



GE-R

Male Connector

24° Flareless / BSPT or BSPP



R (BSPT) thread

Cutting face DIN 3852, form B, G
(BSPP) thread

[CLICK HERE](#)
to go to
GE-R S-Series

L-Series

TUBE FITTING PART #	END SIZE		d3 (mm)	i (mm)	l1 (mm)	L1 (mm)	S1 (mm)	S2 (mm)	STANDARD Pressure Rating (bar)		
	1 (mm)	2 BSPT / BSPP							EO		
									CF	71	MS
GE04LLR	4	R 1/8 keg.	—	8	16.0	26	11	10	100		63
GE06LLR	6	R 1/8 keg.	—	8	14.5	26	11	12	100	100	63
GE08LLR	8	R 1/8 keg.	—	8	16.5	28	12	14	100	100	63
GE08LLR1/4	8	R 1/4 keg.	—	12	20.5	32	14	14	100	100	63
GE10LLR	10	R 1/4 keg.	—	12	20.5	32	14	17	100		63
GE12LLR	12	R 1/4 keg.	—	12	20.0	32	17	19	100		63
GE12LLR3/8	12	R 3/8 keg.	—	12	20.0	32	17	19	100		
GE06LR	6	G 1/8 A	14	8	8.5	23	14	14	315	315	200
GE06LR1/8KEG	6	R 1/8 keg.	—	8	15.0	30	12	14	315		
GE06LR1/4	6	G 1/4 A	18	12	10.0	25	19	14	315	315	200
GE06LR3/8	6	G 3/8 A	22	12	11.5	26	22	14	315		200
GE06LR1/2	6	G 1/2 A	26	14	12.0	27	27	14	315	315	
GE08LR	8	G 1/4 A	18	12	10.0	25	19	17	315	315	200
GE08LR1/8	8	G 1/8 A	14	8	8.5	23	14	17	315	315	
GE08LR1/4KEG	8	R 1/4 keg.	—	12	20.0	35	17	17	315		
GE08LR3/8	8	G 3/8 A	22	12	11.5	26	22	17	315	315	200
GE08LR1/2	8	G 1/2 A	26	14	12.0	27	27	17	315	315	200
GE10LR	10	G 1/4 A	18	12	11.0	26	19	19	315	315	200
GE10LR1/4KEG	10	R 1/4 keg.	—	12	21.0	36	17	19	315		
GE10LR3/8	10	G 3/8 A	22	12	12.5	27	22	19	315	315	
GE10LR1/2	10	G 1/2 A	26	14	13.0	28	27	19	315	315	200
GE12LR	12	G 3/8 A	22	12	12.5	27	22	22	315	315	
GE12LR1/4	12	G 1/4 A	18	12	12.0	27	19	22	315	315	
GE12LR1/4KEG	12	R 1/4 keg.	—	12	22.0	37	19	22	315		
GE12LR3/8KEG	12	R 3/8 keg.	—	12	22.0	37	19	22	315		
GE12LR1/2	12	G 1/2 A	26	14	13.0	28	27	22	315	315	200
GE12LR1/2KEG	12	R 1/2 keg.	—	14	24.0	39	24	22	315		
GE12LR3/4	12	G 3/4 A	32	16	14.0	29	32	22	315		
GE15LR	15	G 1/2 A	26	14	14.0	29	27	27	250	250	160
GE15LR3/8	15	G 3/8 A	22	12	13.5	29	24	27	250	250	160
GE15LR3/8KEG	15	R 3/8 keg.	—	12	23.0	38	24	27	315		
GE15LR1/2KEG	15	R 1/2 keg.	—	14	25.0	40	24	27	315		
GE15LR3/4	15	G 3/4 A	32	16	15.0	30	32	27	250		
GE18LR	18	G 1/2 A	26	14	14.5	31	27	32	250	250	160
GE18LR3/8	18	G 3/8 A	22	12	14.0	29.5	27	32	250		160
GE18LR1/2KEG	18	R 1/2 keg.	—	14	25.5	42	27	32	315		
GE18LR3/4	18	G 3/4 A	32	16	14.5	30	32	32	250	250	
GE22LR	22	G 3/4 A	32	16	16.5	33	32	36	160		100
GE22LR1/2	22	G 1/2 A	26	14	16.5	33	32	36	160	160	100
GE22LR3/4KEG	22	R 3/4 keg.	—	16	29.5	46	32	36	160		
GE28LR	28	G 1 A	39	18	17.5	34	41	41	160	160	100
GE28LR3/4	28	G 3/4 A	32	16	17.5	34	41	41	160		
GE35LR	35	G 1 1/4 A	49	20	17.5	39	50	50	160		100
GE35LR1	35	G 1 A	39	18	17.5	39	46	50	160		
GE42LR	42	G 1 1/2 A	55	22	19.0	42	55	60	160		100

Note: "keg." refers to tapered threads.

Dimensions and pressures for reference only, subject to change.

