

SAFETY VISITOR SPECTACLE G-ONE PLUS

Reference 733442

Safety visitor spectacle with scratch resistant.

Treatment: UV protection.

Lens: 100% polycarbonate. Thickness 2.00 mm.

Temples: 100% polycarbonate.

Colour: clear

Dimensions: (width) 157 mm x (height) 59 mm.

Weight: 44 grams.

Packing:

- carton of 100 units.
- box of 10 units (minimum of order).
- each unit under individual polybag with leaflet.

Advantages

ISO9001 manufacturing ensuring a reliable and durable quality.

No metallic parts. Can be worn over prescription spectacle. Single-piece lens fit perfectly on different face contours and offer wide vision.

Ventilated sidearms. Perforated temples will allow the use of adjustable safety cord.

Conformity

**UK
CA**

This product has been tested according to European Standards **EN166: 2001** (specifications) **EN170: 2002** (ultraviolet filters). It complies with the European Directive **89/686/EEC** on Personal Protective Equipment (PPE) for intermediate design.

EC type examination certificate issued by **BSI** Notified Body **No. 0086**.



Mechanical protection	Symbol FT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality	Symbol 1	Class 1: continuous works (better quality).
Scale number	Symbol 2C.1.2	<p>Colour perception: not impaired</p> <p>Typical application: for use with sources that emit UV radiation predominantly at wavelengths < 313 nm and when glare is not an important factor.</p> <p>This applies to UVC and most UVB radiation ^(b).</p> <p>Typical source ^(a): Low pressure mercury vapour lamps, such as those used to stimulate fluorescent or "black lights", actinic and germicidal lamps.</p> <p>(a) The example given for typical source is for general guidance.</p> <p>(b) The wavelengths of these bands are recommended by IEC (that is UVB 280 nm to 315 nm & 100 nm to 280 nm for UVC).</p>