



Radial insert ball bearings BE30-XL (Series BE)

cylindrical outer ring, with steel aligning ring, P seals on both sides

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	30 mm	
D	72 mm	Before splitting, dimension D corresponds to tolerance class PN according to DIN 620-2
A	21 mm	
B	16 mm	
b	1,9 mm	Tolerance: +0,3/0 Annular slot tolerances to DIN 616 (for snap rings to DIN 5417)
C ₁	14,4 mm	Tolerance: +0,2/0 Annular slot tolerances to DIN 616 (for snap rings to DIN 5417)
D ₁	68,8 mm	Tolerance: 0/-0,5 Annular slot tolerances to DIN 616 (for snap rings to DIN 5417)

m	0,37 kg	Mass
C _r	20700 N	Basic dynamic load rating, radial
C _{0r}	11300 N	Basic static load rating, radial
f ₀	13,8	Calculation factor
C _{ur}	590 N	Fatigue limit load, radial
	206-XL-NPP-B	Designation of bearing
	6206	Reference bearing for determining the equivalent bearing load.

